

[Print](#)

Project Name: ATW UPDATE NOTE RNAV (GPS) RWY 3

Project Reason: UPDATED NOTES TO CURRENT CRITERIA AND VISIBILITY TABLES

Last Updated By: Byron Stubblefield

Last Updated At: 2026-05-12 18:13:37.213625

Status: Verified



!FDC 6/1052 ATW IAP APPLETON INTL, APPLETON, WI. RNAV (GPS) RWY 3, AMDT 1B... LNAV/VNAV VIS ALL CATS RVR 3000. LNAV VIS CAT C/D RVR 5500. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO RVR 5500 AND LNAV CAT C/D VISIBILITY TO 1 3/8 SM. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GRB ALTIMETER SETTING AND INCREASE LPV DA TO 1219 FEET AND ALL VISIBILITIES TO RVR 2600; INCREASE LNAV/VNAV DA TO 1313 FEET AND ALL VISIBILITIES TO RVR 4000; INCREASE ALL MDAS 100 FEET AND LNAV VISIBILITY CAT C/D 3/8 SM AND CIRCLING VISIBILITY CAT C 1/4 SM. CHANGE BARO-VNAV NA NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 54C. CHANGE BARO/VNAV AND VDP NA NOTE TO READ: BARO-VNAV AND VDP NA WHEN USING GRB ALTIMETER SETTING. DELETE NOTE: DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH - GPS. DELETE *LNAV ONLY. DELETE ASTERISK FROM VDP. CHANGE PLANVIEW NOTE TO READ: PROCEDURE NA FOR ARRIVAL AT OSH VORTAC ON AIRWAY RADIALS 337 CW 023. THIS IS RNAV (GPS) RWY 3, AMDT 1C. 2605121813-PERM

Digitally signed by

CASEY D HILL

May 18, 2026