



VOR STANDARD INSTRUMENT APPROACH PROCEDURE  
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

## NOTES, (CONT.):

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BAINBRIDGE ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET. INCREASE S-18 CAT B AND CIRCLING CATS B/D VISIBILITY 1/4 MILE AND S-18 CATS C/D AND CIRCLING CAT C VISIBILITY 1/2 MILE. INCREASE WAPIM FIX MINIMUMS S-18 CATS C/D AND CIRCLING CAT C VISIBILITY 1/4 MILE.

CHART PLANVIEW NOTE: NOPT FOR ARRIVALS ON SZW VORTAC AIRWAY RADIALS 288 CW 088.

QUALITY  
4  
CHECKED

CITY AND STATE

TALLAHASSEE, FL

ELEVATION: 83

THRE: 83

AIRPORT NAME:

TALLAHASSEE RGNL

FACILITY  
IDENTIFIER:

SZW

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR RWY 18, AMDT 12

7 MARCH 2013

SUP:

AMDT: 11B

DATED: 05/05/2011