

**Federal Aviation
Administration**

Transmittal Letter 19-17

June 28, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/15/2019	NC	Wadesboro	Anson County - Jeff Cloud Field	9/0889	6/26/2019	ILS OR LOC RWY 34, Orig-B

AIRAC Date: 15 AUGUST 2019

FDC 9/0889 AFP IAP ANSON COUNTY - JEFF CLOUD FIELD, Wadesboro, NC. ILS OR LOC RWY 34, ORIG-B...
DELETE CIRCLING MINIMUMS. CHART NOTE: RWY 34 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM
NOT AUTHORIZED. DELETE NOTE: WHEN VGSI INOPERATIVE, CIRCLING RWY 16 NA AT NIGHT. CHART
NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROCKINGHAM ALTIMETER SETTING:
INCREASE S-ILS 34 DA TO 607 AND S-ILS 34 ALL CATS VISIBILITY 1/8 SM; INCREASE ALL MDA 60 FEET AND
S-LOC 34 CATS C/D VISIBILITY 1/8 SM AND CILRU FIX MINIMUMS S-LOC 34 CATS C/D VISIBILITY 1/4 SM.
DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROCKINGHAM ALTIMETER
SETTING: INCREASE S-ILS 34 DA TO 607 AND S-ILS 34 ALL CATS VISIBILITY 1/8 MILE; INCREASE ALL MDA
60 FEET AND S-LOC 34 CATS C/D AND CIRCLING CAT C VISIBILITY 1/8 MILE AND CILRU FIX MINIMUMS S-
LOC 34 CATS C/D AND CIRCLING CAT C VISIBILITY 1/4 MILE. THIS IS ILS OR LOC RWY 34, ORIG-C.
1906241355-PERM