

**Federal Aviation
Administration**

Transmittal Letter 22-23

September 16, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
11/3/2022	NC	Wadesboro	Anson County/Jeff Cloud Fld	2/3942	8/5/2022	ILS OR LOC RWY 34, Orig-C

AIRAC Date: 3 NOVEMBER 2022

FDC 2/3942 AFP IAP ANSON COUNTY/JEFF CLOUD FLD, WADESBORO, NC. ILS OR LOC RWY 34, ORIG-C... S-ILS 34 DA 649/HAT 350, VISIBILITY 1 SM ALL CATS. CILRU FIX MINIMUMS S-LOC 34 MDA 820/HAT 521, VISIBILITY CATS C/D 1 1/2 SM. DELETE PLANVIEW NOTE: VGSI AND ILS GIDEPATH NOT COINCIDENT (VGSI ANGLE 3.00/TCH 45). DELETE NOTE: VDP NA WHEN USING ROCKINGHAM ALTIMETER SETTING. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ROCKINGHAM ALTIMETER SETTING: INCREASE S-ILS 34 DA TO 607 AND S-ILS 34 ALL CATS VISIBILITY 1/8 SM; INCREASE ALL MDA 60 FEET AND S-LOC 34 CATS C/D VISIBILITY 1/8 SM AND CILRU FIX MINIMUMS S-LOC 34 CATS C/D VISIBILITY 1/4 SM. DELETE * LOC ONLY, *. DELETE: **LOC ONLY, 1000 WHEN USING ROCKINGHAM ALTIMETER SETTING, **. THIS IS ILS OR LOC RWY 34, ORIG-D. 2206241947-PERM