

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION NDB STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.27								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: MHM NDB							
										CLIMBING RIGHT TURN TO 2500 IN MHM NDB HOLDING PATTERN.							
										ADDITIONAL FLIGHT DATA: HOLD S, RT, 003.00 INBOUND CHART FAS OBST: 1035 TREE 634615N/1522844W CHART 3200 PRIOR TO MHM NDB IN PROFILE CHART AIRPORT ELEV 678, TDZE 678							
1. PT <u> L </u> SIDE OF COURSE <u> 183.00 </u> OUTBOUND <u> 3100 </u> FT WITHIN <u> 10 </u> MILES OF <u> MHM NDB </u> (IAF) 2. _____ 3. FAC <u> 003.00 </u> FAF _____ DIST FAF TO MAP _____ THLD _____ 4. MIN. ALT _____ 8. MSA FROM: MHM NDB 4800														MAG VAR: 21E		EPOCH YEAR: 05	
MINIMUMS																	
TAKEOFF:		STANDARD		X		SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A		#					
CATEGORY ==>		A			B			C			D			E			
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA		
S-3	1600	1 1/4	922	1600	1 1/4	922	1600	2 3/4	922	1600	3	922					
CIRCLING	1600	1 1/4	922	1600	1 1/4	922	1600	2 3/4	922	1600	3	922					
NOTES: CHART NOTE: CIRCLING NA W OF RWY 3-21														#CATS A/B 1000-2, CAT C 1000-2 3/4, CAT D 1000-3			
CITY AND STATE MINCHUMINA, AK				ELEVATION: 678 TDZE: 678 AIRPORT NAME: MINCHUMINA				FACILITY IDENTIFIER: MHM		PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: FEB 16 2006 NDB RWY 3, AMDT 3				SUP NDB OR GPS			
														AMDT 2			
														DATE 11/16/1978			