

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION TACAN OR VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - TITLE 14 CFR PART 97.23								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: KOA VORTAC									
KOA VORTAC		CIGAK/ 11.66 DME		191.00 / 11.66				3500		CLIMBING LEFT TURN TO 2000 ON KOA VORTAC R-294 TO ANDES/11.66 DME AND HOLD.									
ANDES/11.66 DME CCW (IAF)		CIGAK/11.66 DME (NOPT)		11.66 DME ARC				2000											
CIGAK/11.66 DME (IF/IAF)		YUCUV/5.00 DME		011.00 / 6.66 (KOA R-191)				1500											
														ADDITIONAL FLIGHT DATA: HOLD NW, RT, 113.67 INBOUND. FAS OBST: 264 TREE 194259N/1560142W CHART VDP AT 1.21 DME; DISTANCE VDP TO THLD 1.54 MILES. CHART KOA R-294 AT ANDES. FAC CROSSES RWY C/L EXTENDED 5194 FROM THLD. CHART YUCUV TO RW35: 3.37/60					
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)														MAG VAR: 11E EPOCH YEAR:1990					
2. HOLD S CIGAK, RT, 011.00 INBOUND, 2000 FT. IN LIEU OF PT (IAF)																			
3. FAC 011.00 FAF YUCUV/5.00 DME DIST FAF TO MAP <u> </u> THLD <u> </u> 5.32																			
4. MIN. ALT CIGAK 2000, YUCUV 1500																			
8. MSA FROM: KOA VORTAC 080-170 14900, 170-350 3300, 350-080 11500																			
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @									
CATEGORY ➡	A			B			C			D			E						
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA				
S-35	600	1	563	600	1	563	600	1 5/8	563	600	1 5/8	563	600	1 5/8	563				
CIRCLING	600	1	553	600	1	553	600	1 5/8	553	600	2	553	600	2	553				
NOTES:																			
CHART NOTE: CIRCLING NA EAST OF RWY 17-35. @ NA WHEN LOCAL WEATHER NOT AVAILABLE. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT.																			
QUALITY A CHECK																			
CITY AND STATE		ELEVATION: 47 THRE: 37		FACILITY IDENTIFIER:		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP									
KAILUA/KONA, HI		AIRPORT NAME:		KOA		VOR/DME OR TACAN RWY 35, ORIG, 08/25/2011				AMDT NONE									
		KONA INTL AT KEAHOLE				25 AUG 2011				DATE									

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
TACAN OR VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - - TITLE 14 CFR PART 97.23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

QUALITY
A
CHECKED

CITY AND STATE

KAILUA/KONA, HI

ELEVATION: 47

THRE: 37

AIRPORT NAME:

KONA INTL AT KEAHOLE

FACILITY
IDENTIFIER:

KOA

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

VOR/DME OR TACAN RWY 35, ORIG, 08/25/2011

25 AUG 2011

SUP:

AMDT: NONE

DATED: