

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION				RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33				Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.								
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LNAV: RW04						
GUNNE		ZITMU (TF) (FB) (RNP 2.00)			283.66 / 22.38			3000		CLIMB TO 3000 DIRECT EVAJI AND ON TRACK 040.22 TO LAWTO AND HOLD.						
ZITMU (IAF)		YEDUK (NOPT) (TF) (FB) (RNP 1.00)			315.62 / 5.00			3000								
ROD VORTAC (IAF)		YEDUK (NOPT) (TF) (FB) (RNP 1.00)			052.08 / 15.39			3000								
IREJU (IAF)		YEDUK (NOPT) (TF) (FB) (RNP 1.00)			119.32 / 5.97			3000								
YEDUK (IF/IAF) (SEE FORM 8260-10)		UZAZA (TF) (FB) (RNP 1.00)			045.57 / 6.10			2600		ADDITIONAL FLIGHT DATA: HOLD NE, RT, 220.27 INBOUND. CHART FAS OBST: 1244 TREE 403521N/0834106W. UZAZA TO RW04: 3.04/40. CHART LIMA ASOS						
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. HOLD SW YEDUK, RT, 045.57 INBOUND, 3000 FT. IN LIEU OF PT (IAF)																
3. FAC: 045.63 FAF: UZAZA DIST FAF TO MAP: 4.75 THLD: 4.75																
4. MIN. ALT: YEDUK 3000, UZAZA 2600, EYABU/2.00 NM TO RW04 1700																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																
7. GS ANGLE: _____ TCH: 20:1 IS NOT CLEAR 34:1 IS NOT CLEAR																
8. MSA FROM: RW04 3000																
MAG VAR: 6W EPOCH YEAR: 2010																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X						
CATEGORY ==>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	1560	1	531	1560	1	531	1560	1 1/2	531	1560	1 3/4	531				
CIRCLING	1580	1	551	1600	1	571	1600	1 1/2	571	1600	2	571				
NOTES: CHART NOTE: RWY 04 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHART NOTE: PROCEDURE NA AT NIGHT. CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GUNNE ON V144 SOUTHEAST BOUND, V279 SOUTHEAST BOUND. (CONTINUED ON PAGE 2)																
CITY AND STATE KENTON, OH		ELEVATION: 1029 TDZE: 1029 AIRPORT NAME: HARDIN COUNTY				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 4, ORIG-A 24 MAY 2018				SUP: AMDT: ORIG DATED 01/13/2011				

**US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**RNAV - STANDARD**  
**INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

**TERMINAL ROUTES, (CONT.):**

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
UZAZA (FAF)	EYABU/2.00 NM TO RW04 (TF) (FB) (RNP 0.30)	045.63 / 2.75	
EYABU/2.00 NM TO RW04	RW04 (MAP) (TF) (FO) (RNP 0.30)	045.63 / 2.00	
RW04 (MAP)	1429 MSL (CA)	045.63	
1429 MSL	EVAJI (DF) (FB) (RNP 1.00)		
EVAJI	LAWTO (TF) (FO) (RNP 1.00)	040.22 / 6.90	3000

**NOTES, (CONT.):**

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ROSEWOOD VORTAC ON V47 SOUTHBOUND.

CHART NOTE: USE LIMA ALTIMETER SETTING.

PBN REQUIREMENT NOTE: RNP APCH.

QUALITY  
16  
CHECKED

CITY AND STATE

KENTON, OH

ELEVATION: 1029

TDZE: 1029

AIRPORT NAME:

HARDIN COUNTY

FACILITY  
IDENTIFIER:  
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 4, ORIG-A

24 MAY 2018

SUP:

AMDT: ORIG

DATED: 01/13/2011