

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
ILS STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KMYF	<u>PROCEDURE NAME</u> ILS OR LOC RWY 28R	<u>ORIGINAL/AMENDMENT</u> 4D	<u>CITY</u> SAN DIEGO	<u>STATE</u> CA		
<u>AIRPORT ELEVATION</u> 427	<u>TDZE</u> 423	<u>SUPERSEDED</u> ILS OR LOC RWY 28R	<u>ORIGINAL/AMENDMENT</u> 4C	<u>DATED</u> 02/28/2019	<u>MAG VAR</u> 14E	<u>EPOCH YEAR</u> 1980
<u>FACILITY</u> I-MYF	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 22 APRIL 2021	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
BARET INT/MZB 27.72 DME		OGOTE INT/MZB 23.45 DME					255.85	4.27 (MZB R-076)	6100
OGOTE INT/MZB 23.45 DME		BAKEL INT/MZB 19.28 DME					255.85	4.17 (MZB R-076)	5900
BAKEL INT/MZB 19.28 DME	IAF	MIBBY INT/I-MYF 14.51 DME/RADAR					196.00	4.21 (JLI R-196)	4200
MIBBY INT/I-MYF 14.51 DME/RADAR	IF	NESTY/I-MYF 11.22 DME/RADAR					280.99	3.29 (I-MYF)	3600
NESTY/I-MYF 11.22 DME/RADAR		PENYY/I-MYF 6.97 DME/RADAR					280.99	4.25 (I-MYF)	2500

MISSED APPROACH

MAP:

ILS: DA
LOC: 6.29 NM AFTER PENYY/I-MYF 6.97 DME/RADAR OR AT I-MYF 0.68 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1100 THEN CLIMBING LEFT TURN TO 3000 ON HEADING 270 AND MZB VORTAC R-326 TO CARIF INT/MZB 16.28 DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS (DO NOT CHART):

CLIMB TO 1100 THEN CLIMBING LEFT TURN TO 3000 ON HEADING 270 AND OCN VORTAC R-145 TO CARIF INT/OCN 12.84 DME AND HOLD.



CHANGES - REASONS

1. ADDED CHART NOTE: CIRCLING RWY 10L, 23, 28L NA AT NIGHT. - UNLIT 20:1 PENETRATIONS EXIST TO RWY 10L, 23, AND 28L, IAW 8260-19I.
2. ADDED CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO S-ILS ALL CATS. - IAW 8260.19I.
3. ADDED CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 28R ALL CATS VISIBILITY TO 1SM. - IAW 8260.19I.
4. CHANGED ALTERNATE MINS FROM "ILS: STANDARD.; LOC: STANDARD." TO "ILS: STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED.; LOC: STANDARD - NA WHEN LOCAL WEATHER NOT AVAILABLE., NA WHEN CONTROL TOWER CLOSED." - PENDING AIRNAV DATA.

COORDINATED WITH:

A4A **ALPA** **AOPA** **APA** **HAI** **NBAA** **OTHER:** SAN DIEGO APCH, MYF TOWER

FLIGHT CHECKED BY

PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJF-10) MEMO, APRIL 29, 2020, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE

DATE

Digitally signed by

DEVELOPED BY

DONALD H. LANIER (ZACHARY KRUEGER)

Digitally signed by
DONALD H LANIER

DONALD H LANIER

Feb 18, 2021

OFFICE

AJV-A431

DATE

12/14/2020

APPROVED BY

LONNIE EVERHART

Digitally signed by
DONALD H LANIER
Feb 18, 2021

OFFICE

AJV-A430

DATE

TITLE
MANAGER

