U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION

VOR/DME

STANDARD INSTRUMENT APPROACH PROCEDURE

FLIGHT STANDARDS SERVICE - FAR PART 97. 23

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
LAS VORTAC	KACCY/LAS 16.50 DME	180.01/16.50	7100
BLD VORTAC	KACCY	224.86/21.66	7100
KACCY	CINDA/LAS 12.50 DME	000.01/4.00 (LAS R-180)	6100
CINDA	NICZU/LAS 9.50 DME	000.01/3.00 (LAS R-180)	5200

MISSED APPROACH

MAP: LAS R-180/0.4

CLIMB TO 5000 THEN CLIMBING RIGHT TURN TO 6000 DIRECT BLD VORTAC AND HOLD.

ADDITIONAL FLIGHT DATA:

HOLD SE, RT, 330 INBOUND

FAS OBST: 2608 TWR 360051/1150937

CHART: 3291 TERRAIN 355533/1151430

1. PT NA SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. HOLD S KACCY, RT, 000.01 INBOUND, 7100 FT IN LIEU OF PT (IAF)
3. FAC 000.01 FAF NICZU DIST FAF TO MAP - THLD -
4. MIN. ALT KACCY 7100 ,CINDA 6100, NICZU 5200, LAS R-180/5.50 3780
8. MSA FROM: LAS VORTAC 030-120 6700, 120-210 8300, 210-300 13200, 300-030 10200

MAG VAR: 15E EPOCH YEAR: 80

MINIMUMS

TAKEOFF: [ ] STANDARD [X] SEE FAA FORM 8260-15 FOR THIS AIRPORT ALTERNATE: N A [ ] STANDARD #

CATEGORY	A			B			C			D			E		
	MDA	VIS	HAT/HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA	MDA	VIS	HAT/ HAA
CIRCLING	3020	1	838	3020	1 1/4	838	3020	2 1/2	838	3020	2 3/4	838			

NOTES:

CAT C 900-2½.
CAT D 900-2 3/4
#CAT A/B 900-2

THIS IS A CORRECTED COPY OF THIS PROCEDURE PUSLISHED IN TL00-17.

CITY AND STATE	ELEVATION: 2182 TDZE: AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP
LAS VEGAS, NV	McCARRAN INTL	LAS	OCT -5 2000 VOR/DME-A, ORIG.	AMDT NONE
				DATED