

**Federal Aviation
Administration**

Transmittal Letter 20-22

September 4, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

| AIRAC DATE | STATE | CITY | AIRPORT | FDC NUMBER | FDC DATE | SUBJECT |
|------------|-------|-----------|-------------------|------------|-----------|-------------------------------|
| 10/8/2020 | CA | Red Bluff | Red Bluff Muni | 0/5587 | 8/27/2020 | RNAV (GPS) RWY 15, Amdt 1A |

AIRAC Date: 8 OCTOBER 2020

FDC 0/5587 RBL IAP RED BLUFF MUNI, RED BLUFF, CA. RNAV (GPS) RWY 15, AMDT 1A...
LNAV/VNAV DA: 788/HAT 436 HAT, VIS 1 1/4 SM ALL CATS. DELETE NOTE: FOR
UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -5C (23F) OR ABOVE
54C (130F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV
NA BELOW -2C OR ABOVE 54C. DELETE NOTE: DME/DME RNP-0.3 NA. PBN
REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING
NOT RECEIVED; USE REDDING ALTIMETER SETTING AND INCREASE ALL DA/MDA 80
FEET AND INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/4 MILE, INCREASE
LNAV CAT C/D AND CIRCLING CAT C VISIBILITY 1/4 SM. CHART NOTE: WHEN LOCAL
ALTIMETER SETTING NOT RECEIVED; USE REDDING ALTIMETER SETTING AND
INCREASE LPV DA TO 674 FEET AND INCREASE LNAV/VNAV DA TO 860 FEET AND
INCREASE VISIBILITY ALL CATS 1/8 SM; INCREASE ALL MDAS 80 FEET AND LNAV
VISIBILITY CATS C/D 1/8 SM AND CIRCLING VISIBILITY CATS C/D 1/4 SM. THIS IS RNAV
(GPS) RWY 15, AMDT 1B. 2008211258-PERM