

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LP: RW07 LNAV: RW07					
FOSAT (IF/IAF)		APIGE (FB)		068.06 / 5.00				2700		CLIMB TO 3000 DIRECT GLAKE AND HOLD.					
APIGE (FAF)		DOLSE/2.80 NM TO RW07 (FB)		068.13 / 2.52											
DOLSE/2.80 NM TO RW07		RW07 (MAP) (FO)		068.13 / 2.80											
RW07 (MAP)		1366 MSL		068.13											
1366 MSL		GLAKE (FO)						3000		ADDITIONAL FLIGHT DATA: HOLD E, RT, 248.36 INBOUND. CHART FAS OBST: 1211 TREE 435718N/0903106W CHART FAS OBST: 1177 TOWER 435807N/0903052W WAAS CHANNEL # 97737 REFERENCE PATH ID: W07A APIGE TO RW07: 3.00/40. CHART CIRCLING ICON. CHART KVOK CTAF. CHART R-6904A. CHART VOLK SOUTH MOA. CHART VOLK WEST MOA. CHART VOLK EAST MOA. CHART FALLS 1 MOA. CHART FALL 2 MOA. CHART R-6901A. (SEE FORM 8260-10)					
1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)															
2. HOLD W FOSAT, RT, 068.06 INBOUND, 3000 FT. IN LIEU OF PT (IAF)															
3. FAC: 068.13 FAF: APIGE DIST FAF TO MAP: 5.32 THLD: 5.32															
4. MIN. ALT: FOSAT 3000, APIGE 2700, DOLSE/2.80 NM TO RW07 1880															
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:															
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:															
7. GS ANGLE: TCH: 34:1 IS NOT CLEAR															
8. MSA FROM:										MAG VAR: 0E EPOCH YEAR: 2000					
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X					
CATEGORY ==>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	1460	1	494	1460	1	494	1460	1 3/8	494		NA				
LNAV MDA	1500	1	534	1500	1	534	1500	1 1/2	534		NA				
CIRCLING	1540	1	574	1560	1	594	1660	2	694		NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: USE CAMP DOUGLAS ALTIMETER SETTING; WHEN NOT RECEIVED, USE SPARTA/FORT MCCOY ALTIMETER SETTING AND INCREASE ALL MDA 20 FEET, INCREASE LNAV CAT C VISIBILITY 1/8 MILE. (SEE FORM 8260-10)															
CITY AND STATE TOMAH, WI		ELEVATION: 966 TDZE: 966 AIRPORT NAME: BLOYER FIELD				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG 10 DECEMBER 2015				SUP: AMDT: NONE DATED			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ADDITIONAL FLIGHT DATA, (CONT.):

CHART R-6901B.

CHART R-6904B.

LTP HAE: 260.5 M

NOTES, (CONT.):

CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.

CHART NOTE: PROCEDURE NA AT NIGHT.

CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT(VGSI ANGLE {ANGLE}/TCH {FEET}).

CHART PLANVIEW NOTE: WHEN RESTRICTED AREAS R-6901B ACTIVE (HOT/IN USE) PROCEDURE MAY NOT BE AVAILABLE.

TAA

	FROM	TO	ALT
1.	338/30 CW 158/30 (NOPT)	338/15 CW 158/15	3500
	338/15 CW 158/15	FOSAT (IF/IAF) (FB)	3000
2.	158/30 CW 338/30	158/8 CW 338/8	3200
	158/8 CW 338/8	FOSAT (IF/IAF) (FO)	3000

QUALITY
16
CHECKED

CITY AND STATE

TOMAH, WI

ELEVATION: 966

TDZE: 966

AIRPORT NAME:

BLOYER FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 7, ORIG
10 DECEMBER 2015

SUP:

AMDT: **NONE**

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	Y72
RUNWAY	RW07
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W07A
LTP/FTP LATITUDE	435827.2690N
LTP/FTP LONGITUDE	0902914.9965W
LTP/FTP ELLIPSOIDAL HEIGHT	+02605
FPAP LATITUDE	435900.3300N
FPAP LONGITUDE	0902720.4075W
THRESHOLD CROSSING HEIGHT (TCH)	00040.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1560
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0

<u>CRC REMAINDER</u>	77CC671B
----------------------	----------

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K5
LTP ORTHOMETRIC HEIGHT	+02944
FPAP ORTHOMETRIC HEIGHT	+02944

QUALITY
16
CHECKED

CITY AND STATE

TOMAH, WI

ELEVATION: 966

TDZE: 966

AIRPORT NAME:

BLOYER FIELD

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 7, ORIG

10 DECEMBER 2015

SUP:

AMDT:

NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION <u>RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE</u> FLIGHT STANDARDS SERVICES - FAR PART 97.33	Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	---

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION <u>RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE</u> FLIGHT STANDARDS SERVICES - FAR PART 97.33	Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	---



CITY AND STATE TOMAH, WI	ELEVATION: 966 TDZE: 966	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG 10 DECEMBER 2015	SUP:
	AIRPORT NAME: BLOYER FIELD			AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION								Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.				
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE												
FLIGHT STANDARDS SERVICES - FAR PART 97.33												
ARINC SUMMARY - 424-18 - RNAV (GPS)												
ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	FOSAT	FOSAT	010	IAF	HF	R	FO		068.1 (068.1T)	004.0	AA 03000	
		FOSAT	010	FACF	IF		FB				AA 03000	
		APIGE	020	FAF	TF		FB	0.5	068.1 (068.1T)	005.0	AA 02700	
		DOLSE	021	SDF	TF		FB	0.3	068.1 (068.1T)	002.5	AA 01880	GS 01897
		RW07	030	MAP	TF		FO	0.3	068.1 (068.1T)	002.8	AT 01006	
MISSED APPROACH		FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
			040		CA		FB		068.1 (068.1T)		AA 01366	
		GLAKE	050		DF		FO				AA 03000	
		GLAKE	060		HM	R	FO		248.4 (248.4T)	004.0	AA 03000	
POINT DATA		WAYPOINT			LAT IN SECS		LONG IN SECS		LAT IN MINS		LONG IN MINS	
		APIGE			N435628.57		W0903605.22		N4356.476		W09036.087	
		DOLSE			N435724.84		W0903250.96		N4357.414		W09032.849	
		FOSAT			N435436.63		W0904230.36		N4354.611		W09042.506	
		GLAKE			N440216.96		W0901555.84		N4402.283		W09015.931	
		RW07			N435827.27		W0902915.00		N4358.455		W09029.250	
RUNWAY DATA				THRESHOLD								
		RWY		ELEVATION		TCH						
		RW07		00966		40						



CITY AND STATE TOMAH, WI	ELEVATION: 966	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS) RWY 7, ORIG 10 DECEMBER 2015	SUP:
	AIRPORT NAME: BLOYER FIELD			AMDT: NONE
				DATED: