

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> I17	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 26	<u>ORIGINAL/AMENDMENT</u> 1B	<u>CITY</u> PIQUA	<u>STATE</u> OH
<u>AIRPORT ELEVATION</u> 993	<u>TDZE</u> 986	<u>SUPERSEDED</u> RNAV (GPS) RWY 26	<u>ORIGINAL/AMENDMENT</u> 1A	<u>DATED</u> 09/07/2023
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 19 MARCH 2026	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>MAG VAR</u> 6W
				<u>EPOCH YEAR</u> 2005
				<u>CANCEL/SUSPEND</u>

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
BONEE	IAF	IMOSE	NOPT	TF	FB	1.00	331.22	11.35	2800
ROD VORTAC	IAF	IMOSE	NOPT	TF	FB	1.00	210.08	5.25	2800
IMOSE	IF/IAF	ZALAD		TF	FB	1.00	261.66	5.10	2600
ZALAD	FAF	WUNRI/1.81 NM TO RW26		TF	FB	0.30	261.59	3.14	
WUNRI/1.81 NM TO RW26		RW26	MAP	TF	FO	0.30	261.59	1.81	
RW26	MAP	1213 MSL		CA			261.59		
1213 MSL		MANUE		DF	FO	1.00			2700

MISSED APPROACH

MAP:

LPV: DA
LNAV/VNAV: DA
LNAV: RW26

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 2700 DIRECT MANUE AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT	SIDE OF COURSE	OUTBOUND	FT WITHIN	MILES OF	(IAF)
2. HOLD E IMOSE, RT, 261.68 INBOUND, 2800 IN LIEU OF PT (IAF), MAX 6000.					
3. FAC: 261.59	FAF: ZALAD		DIST FAF TO MAP: 4.95	DIST FAF TO THLD: 4.95	
4. MIN ALT: IMOSE 2800, ZALAD 2600, WUNRI/1.81 NM TO RW26 1600					
5. DIST TO THLD FROM OM:	MM:	IM:	150 HAT:	227 HAT: 0.67	GS ANT:
6. MIN GP INCPT: 2600	GP ALT AT PFAF: ZALAD 2600			OM:	MM:
7. GP ANGLE: 3.00	34:1: IS CLEAR	20:1: IS CLEAR	TCH: 37.4		IM:
8. MSA FROM: RW26 3100					

PBN REQUIREMENTS NOTE:

RNP APCH - GPS.

NOTES:

CHART NOTE: BARO-VNAV NA.

CHART NOTE: USE VES ALTIMETER SETTING.

ADDITIONAL FLIGHT DATA:

CHART VES AWOS-3PT.

HOLD W, RT, 081.38 INBOUND.

FAS OBST: 1101 TREE 401015N/0841827W.

WAAS CHANNEL # 86745

REFERENCE PATH ID: W26A

LTP HAE: 267.2 M

MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☒

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
LPV DA	1213	1	227	1213	1	227	1213	1	227		NA				
LNAV/VNAV DA	1296	1	310	1296	1	310	1296	1	310		NA				
LNAV MDA	1380	1	394	1380	1	394	1380	1 1/8	394		NA				
CIRCLING	1440	1	447	1560	1	567	1560	1 1/2	567		NA				

CHANGES - REASONS

1. ADDITIONAL FLIGHT DATA: REMOVED CIRCLING ICON - NO LONGER REQUIRED.
2. ADDITIONAL FLIGHT DATA: CHANGED FROM CHART FAS OBST: 1099 TREE 401008N/0841818W TO FAS OBST: 1101 TREE 401015N/0841827W - UPDATED EVALUATION.
3. MINIMUMS: CIRCLING CAT B MDA/HAA INCREASED FROM 1540 MDA/547 TO 1560 MDA/567 HAA - NEW CONTROLLING OBSTACLE, CANCELS NOTAM 5/1205.
4. CHANGED CHART NOTE FROM USE VERSAILLES ALTIMETER SETTING TO USE VES ALTIMETER SETTING - 8260.19K. 8-6-10.F(6).
5. CRC REMAINDER CHANGED FROM 4CEFF194 TO B310DCB9 - THE VERTICAL ALERT LIMIT CHANGED FROM 50.0 TO 35.0, LPV HAT IS LESS THAN 250.
6. ADDITIONAL FLIGHT DATA: CHANGED FROM "CHART VERSAILLES AWOS-3PT" TO "CHART VES AWOS-3PT" - IAW 8260.19K 8-2-4.B(3).



COORDINATED WITH:

A4A

☐

ALPA

☒

AOPA

☒

APA

☐

HAI

☐

NBAA

☒

OTHER: DAY APP CON, ZID, AMGR

FLIGHT CHECKED BY

SCOTT WIEBE

Digitally signed by

OFFICE

DATE

RAKE MCGRAW

AJF

01/09/2026

Jan 12, 2026

DEVELOPED BY

RAYMOND JOHNSON

Digitally signed by

OFFICE

DATE

RAKE MCGRAW

AJV-A422

Jan 12, 2026

APPROVED BY

RAKE MCGRAW

Digitally signed by

OFFICE

DATE

TITLE

RAKE MCGRAW

AJV-A422

MANAGER

Jan 12, 2026

FAS DATA BLOCK INFORMATION

DATA FIELD
OPERATION TYPE
SBAS SERVICE PROVIDER IDENTIFIER
AIRPORT IDENTIFIER
RUNWAY
APPROACH PERFORMANCE DESIGNATOR
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR
REFERENCE PATH IDENTIFIER (APPROACH ID)
LTP/FTP LATITUDE
LTP/FTP LONGITUDE
LTP/FTP ELLIPSOIDAL HEIGHT
FPAP LATITUDE
FPAP LONGITUDE
THRESHOLD CROSSING HEIGHT (TCH)
TCH UNITS SELECTOR (METERS OR FEET USED)
GLIDEPATH ANGLE (GPA)
COURSE WIDTH AT THRESHOLD
LENGTH OFFSET
HORIZONTAL ALERT LIMIT (HAL)
VERTICAL ALERT LIMIT (VAL)

DATA
0
0
I17
RW26
0
0
W26A
400957.8155N
0841805.4180W
+02672
400935.5135N
0841957.9430W
00037.4
F
03.00
106.75
1528
40.0
35.0

CRC REMAINDER B310DCB9

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K5
LTP ORTHOMETRIC HEIGHT +03001
FPAP ORTHOMETRIC HEIGHT +03001

