

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
KRITR	EIGHT	KRITR8.KRITR	SEVEN	05/14/2026	9 JUL 2026
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
☐	☐	☒	☐	☐	☒

DP ROUTE DESCRIPTION:

CLT:

TAKEOFF RWY 19L: CLIMB ON HEADING 182.96 TO 1260, THEN ON HEADING 182.96 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO JDEAN, THENCE...
TAKEOFF RWY 18L: CLIMB ON HEADING 182.97 TO 1260, THEN ON HEADING 182.97 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO JDEAN, THENCE...
TAKEOFF RWY 19R: CLIMB ON HEADING 182.96 TO 1260, THEN ON HEADING 200.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO JDEAN, THENCE...
TAKEOFF RWY 1R: CLIMB ON HEADING 002.96 TO 1260, THEN ON HEADING 330.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO JDEAN, THENCE...
TAKEOFF RWY 1L: CLIMB ON HEADING 002.96 TO 1260, THEN ON HEADING 315.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO JDEAN, THENCE...
TAKEOFF RWY 36R: CLIMB ON HEADING 002.97 TO 1260, THEN ON HEADING 025.00 OR AS ASSIGNED BY ATC FOR RADAR VECTORS TO JDEAN, THENCE...

...ON TRACK 022.19 TO KRITR, THEN ON ASSIGNED TRANSITION. MAINTAIN 8000. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

JQF:

TAKEOFF RWY 2: CLIMB ON HEADING 016.46 TO 2200, THEN ON HEADING ASSIGNED BY ATC, THENCE...
TAKEOFF RWY 20: CLIMBING LEFT TURN HEADING 150.00 TO 2400, THEN ON HEADING ASSIGNED BY ATC, THENCE...

AKH:

TAKEOFF RWY 3: CLIMB ON HEADING 049.34 TO 2700 BEFORE TURNING LEFT, THEN ON HEADING ASSIGNED BY ATC, THENCE...
TAKEOFF RWY 21: CLIMB ON HEADING 214.33 TO 1600 BEFORE PROCEEDING NORTH, THEN ON HEADING ASSIGNED BY ATC, THENCE...

IPJ:

TAKEOFF RWY 5: CLIMB ON HEADING 063.15 TO 2000 BEFORE PROCEEDING ON COURSE, THEN ON HEADING ASSIGNED BY ATC, THENCE...
TAKEOFF RWY 23: CLIMB ON HEADING 243.16 TO 2800 BEFORE TURNING LEFT, THEN ON HEADING ASSIGNED BY ATC, THENCE...

RUQ:

TAKEOFF RWY 2: CLIMB ON HEADING ASSIGNED BY ATC, THENCE...
TAKEOFF RWY 20: CLIMB ON HEADING 201.99 TO 1700 BEFORE TURNING RIGHT, THEN ON HEADING ASSIGNED BY ATC, THENCE...

...FOR RADAR VECTORS TO JDEAN, THEN ON TRACK 022.19 TO KRITR, THEN ON ASSIGNED TRANSITION. MAINTAIN 3000. EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

DEPARTING EQY, LKR, VUJ, AND UZA: CLIMB ON HEADING ASSIGNED BY ATC FOR RADAR VECTORS TO JDEAN, THEN ON TRACK 022.19 TO KRITR, THEN ON ASSIGNED TRANSITION. MAINTAIN 3000, EXPECT FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
FILDS	KRITR8.FILDS	KRITR	FILDS	TRACK 016.17	54.47	16200	5900	
SMIAM	KRITR8.SMIAM	KRITR	SMIAM	TRACK 022.98	15.17	8300	3600	

PBN REQUIREMENT NOTES:

RNAV 1 - DME/DME/IRU OR GPS.



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
KRITR	EIGHT	KRITR8.KRITR	SEVEN	05/14/2026	9 JUL 2026

EQUIPMENT REQUIREMENT NOTES:

RADAR REQUIRED.

PROCEDURAL DATA NOTES:

NOTE: TURBOJET ONLY.

NOTE: TRANSPONDER CODE WILL BE ISSUED VIA PDC OR CLT CLNC DEL.

NOTE: IF UNABLE TO ACCEPT CLIMB RATES, ADVISE ATC ON INITIAL CONTACT.

NOTE: CLT ONLY: ACCELERATE TO 250 KIAS, IF UNABLE ADVISE ATC. UPON REACHING 10000 MSL, ACCELERATE TO AND MAINTAIN 280 KIAS, IF UNABLE ADVISE ATC.

NOTE: ALL OTHER AIRPORTS: UPON REACHING 10000 MSL, ACCELERATE TO AND MAINTAIN 280 KIAS, IF UNABLE ADVISE ATC.

TAKEOFF MINIMUMS:

CLT:

RWY 19L, 18L, 19R, 1R, 36R: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1260.

RWY 1L: STANDARD WITH MINIMUM CLIMB OF 500 FT/NM TO 1400.

JQF:

RWY 2: STANDARD.

RWY 20: STANDARD WITH MINIMUM CLIMB OF 320 FT/NM TO 2400.

AKH:

RWY 3, 21: STANDARD.

EQY:

RWY 5, 23: STANDARD.

IPJ:

RWY 5, 23: STANDARD.

LKR:

RWY 6, 24: STANDARD.

VUJ:

RWY 4L, 22R: NA - ENVIRONMENTAL.

RWY 22L: STANDARD

RWY 4R: 300-1 3/4 OR STANDARD WITH MINIMUM CLIMB OF 315 FT/NM TO 1000.

RUQ:

RWY 2: STANDARD.

RWY 20: 400-2 3/4 OR STANDARD WITH MINIMUM CLIMB OF 205 FT/NM TO 1300, OR ALTERNATIVELY, WITH STANDARD TAKEOFF MINIMUMS AND A NORMAL 200 FT/NM CLIMB GRADIENT, TAKEOFF MUST OCCUR NO LATER THAN 1200 FT PRIOR TO DER.

UZA:

RWY 2, 20: STANDARD.

TAKEOFF OBSTACLES NOTES:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

CLT:

RWY 1L: 2748 FT MSL TOWER 352145.00N/0810918.00W.

JQF:

RWY 20: 1950 FT MSL TOWER 351715.00N/0804144.00W.



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
KRITR	EIGHT	KRITR8.KRITR	SEVEN	05/14/2026	9 JUL 2026

VUJ:

RWY 4R: 732 FT MSL TREE (37-111225) 352557.53N/0800829.12W (CLIMB GRADIENT), 803 FT MSL TREE (37-112801) 352620.07N/0800816.77W (CLIMB TO ALTITUDE), 820 FT MSL TREE (37-116182) 352627.52N/0800810.70W (CEILING), 790 FT MSL (37-114938) 352637.40N/0800804.59N (VISIBILITY).

RUQ:

RWY 20: 1121 FT MSL TOWER 353613.00N/0803234.12W.

MSA:

CLT, 3800

JQF, 3800

AKH, 3800

EQY, 3100

IPJ, 3800

LKR, 2300

VUJ, 3100

RUQ, 3400

UZA, 3800

LOST COMMUNICATIONS PROCEDURES:**ADDITIONAL FLIGHT DATA:**

AIRPORT MV: CLT (P) 7W/2000, JQF 6W/1995, AKH 6W/2000, EQY 6W/1990, IPJ 6W/1995, LKR 7W/2000, VUJ 6W/1985, RUQ 6W/1985, UZA 5W/1990.

DME/DME ASSESSMENT: SAT (RNP 2.0).

CLT - CHART: TOP ALTITUDE 8000

JQF, AKH, EQY, IPJ, LKR, VUJ, RUQ, UZA - CHART: TOP ALTITUDE 3000.

AIRPORTS SERVED:

<u>AIRPORT ID</u>	<u>CITY</u>	<u>STATE</u>
CLT	CHARLOTTE	NC
JQF	CONCORD	NC
AKH	GASTONIA	NC
EQY	MONROE	NC
IPJ	LINCOLNTON	NC
LKR	LANCASTER	SC
VUJ	ALBEMARLE	NC
RUQ	SALISBURY	NC
UZA	ROCK HILL	SC

COMMUNICATIONS:

CLT: CHART: ATIS, CLNC DEL, GND CON, TOWER, CPDLC.

JQF: CHART: ATIS, CLNC DEL, GND CON, TOWER, UNICOM.

AKH: CHART: ASOS, CLNC DEL, UNICOM.

EQY: CHART: ASOS, CLNC DEL, UNICOM.



<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
KRITR	EIGHT	KRITR8.KRITR	SEVEN	05/14/2026	9 JUL 2026

IPJ: CHART: AWOS, CLNC DEL (GCO), UNICOM.
LKR: CHART: AWOS, GCO, UNICOM.
VUJ: CHART: ATIS, CLNC DEL, GND CON, TOWER.
RUQ: CHART: AWOS, CLNC DEL, UNICOM.
UZA: CHART: ASOS, CLNC DEL, UNICOM

FIXES AND/OR NAVAIDS:**REMARKS:**

CHART: NOTE: (CLT ONLY) SEE ADDITIONAL REQUIREMENTS ON AAUP.
JQF RWY 20 CLIMB GRADIENT ROUNDED TO 320 FT PER NM FOR PUBLICATION (COMPUTED VALUE 317 FT PER NM).
RUQ RWY 20 CLIMB GRADIENT ROUNDED TO 205 FT PER NM FOR PUBLICATION (COMPUTED VALUE 202 FT PER NM).
CONTROLLING OBSTRUCTIONS: KRITR TO FILDS: 37-001286, KRITR TO SMIAM: 37-022334, JDEAN TO KRITR: 37-001216.
ABBREVIATED AMENDMENT.
CLT, AKH, EQY, IPJ, JQF, LKR, RUQ, UZA, VUJ: ORDER 8260.3G, LEGACY ICA USED FOR DESIGN AND EVALUATION.

FLIGHT INSPECTED BY**SIGNATURE****OFFICE****DATE**

PROCESSED IAW TECHNICAL SUPPORT (AJF-17) MEMO DATED 07/07/2021, SUBJECT: GUIDANCE FOR PROCEDURAL CHANGES REQUIRING FLIGHT INSPECTION/VALIDATION.

Digitally signed by

DEVELOPED BY**SIGNATURE**

CASIMIR L TABAKA

OFFICE**DATE**

JAMIE KUNKLER

Digitally signed by

CASIMIR L TABAKA

Feb 18, 2026

AJV-A432

12/19/2025

Feb 18, 2026

APPROVED BY**SIGNATURE**

Digitally signed by

CASIMIR L TABAKA

OFFICE**DATE****TITLE**

CASIMIR L. TABAKA

AJV-A432

MANAGER

REQUIRED EFFECTIVE DATE

Feb 18, 2026

ROUTINE

COORDINATED WITH:

A4A ☒ **ALPA** ☒ **AOPA** ☒ **APA** ☒ **HAI** ☐ **NBAA** ☒ **OTHER:**ZTL, CLT APP CON, CLT ATCT, JQF ATCT, VUJ ATCT, AMGR(S).

CHANGES - REASONS:

1. CLT RWYS 36C/18C CHANGED TO RWYS 1R/19L - RUNWAY RENUMBERING.
2. REMARKS: ADDED CLT, AKH, EQY, IPJ, JQF, LKR, RUQ, UZA, VUJ: ORDER 8260.3G, LEGACY ICA USED FOR DESIGN AND EVALUATION - IAW 8260.46K PARA 2-1-1.I.

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

DP NAME				NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED		ACTUAL EFFECTIVE DATE	
KRITR				EIGHT		KRITR8.KRITR		SEVEN		05/14/2026		9 JUL 2026	
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS				
RW19L (AER)	351338.63N/0805711.41W	N	-	-	-	-							
1260 MSL		-	-	VA	175.96	-	AT/ABOVE 1260		CG 500 FT/NM TO 1260				
		-	-	VM	175.96	-							
RW18L (AER)	351329.04N/0805610.17W	N	-	-	-	-							
1260 MSL		-	-	VA	175.97	-	AT/ABOVE 1260		CG 500 FT/NM TO 1260				
		-	-	VM	175.97	-							
RW19R (AER)	351331.02N/0805802.71W	N	-	-	-	-							
1260 MSL		-	-	VA	175.96	-	AT/ABOVE 1260		CG 500 FT/NM TO 1260				
		-	-	VM	193.00	-							
RW01R (AER)	351159.97N/0805702.92W	N	-	-	-	-							
1260 MSL		-	-	VA	355.96	-	AT/ABOVE 1260		CG 500 FT/NM TO 1260				
		-	-	VM	323.00	-							
RW01L (AER)	351202.23N/0805755.07W	N	-	-	-	-							
1260 MSL		-	-	VA	355.96	-	AT/ABOVE 1260		CG 500 FT/NM TO 1400				
		-	-	VM	308.00	-							
RW36R (AER)	351203.44N/0805602.82W	N	-	-	-	-							
1260 MSL		-	-	VA	355.97	-	AT/ABOVE 1260		CG 500 FT/NM TO 1260				
QUALITY													



<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>ACTUAL EFFECTIVE DATE</u>
KRITR		EIGHT		KRITR8.KRITR		SEVEN		05/14/2026	9 JUL 2026
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
		-	-	VM	018.00	-			
JDEAN	353447.60N/0805738.66W	Y	-	IF	-	-			
KRITR	354121.47N/0805527.55W	Y	FB	TF	015.19	6.79			
KRITR	354121.47N/0805527.55W	Y	-	IF	-	-			KRITR8.SMIAM
SMIAM	355557.49N/0805019.14W	Y	FB	TF	015.98	15.17			
KRITR	354121.47N/0805527.55W	Y	-	IF	-	-			KRITR8.FILDS
FILDS	363511.96N/0804441.06W	Y	FB	TF	009.17	54.47			