

**Federal Aviation
Administration**

Transmittal Letter 22-22

September 2, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/6/2022	VA	Leesburg	Leesburg Exec	2/4451	8/23/2022	RNAV (GPS) RWY 17, Amdt 3B

AIRAC Date: 6 OCTOBER 2022

FDC 2/4451 JYO IAP LEESBURG EXEC, LEESBURG, VA. RNAV (GPS) RWY 17, AMDT 3B... APT ELEV 390. LPV VIS ALL CATS 3/4. LNAV/VNAV VIS ALL CATS 7/8. LNAV VIS CATS A/B 3/4, CATS C/D 1 3/8. CIRCLING CAT A/B HAA 550, CIRCLING CAT C MDA 1040/HAA 650, CAT D MDA 1300/HAA 910, CAT C VIS 1 3/4, CAT D VIS 3. CHANGE NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15 C OR ABOVE 41 C. DELETE NOTE: WHEN VGSI INOP, STRAIGHT-IN/CIRCLING RWY 17 PROCEDURE NA AT NIGHT. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE NOTE: DME/DME RNP-0.3 NA. DELETE NOTE: *LNAV ONLY. DELETE ASTERISK FROM MINIMUM ALTITUDE AT CEYAC/2.70 NM TO RW17 1280. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WASHINGTON DULLES INTL ALTIMETER SETTING: INCREASE LPV DA TO 665 FEET; INCREASE LNAV/VNAV DA TO 757 FEET AND INCREASE ALL VISIBILITIES 1/8 SM; INCREASE ALL MDA 40 FEET AND VISIBILITY LNAV CAT C/D AND CIRCLING CAT C 1/4 SM. DELETE NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LNAV CATS A/B. CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LPV ALL CATS. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. DELETE NOTE: FOR INOPERATIVE ODALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 1 1/8 AND LNAV CATS C/D VISIBILITY TO 1 5/8. CHART NOTE: FOR INOPERATIVE ALS, INCREASE VISIBILITY LNAV/VNAV CATS A/B TO 1 AND LNAV CATS C/D TO 1 5/8. CHANGE NOTE TO READ: FOR INOPERATIVE ALS WHEN USING WASHINGTON DULLES INTL ALTIMETER SETTING, INCREASE VISIBILITY LPV CATS A/B TO 7/8 SM AND INOPERATIVE TABLE DOES NOT APPLY TO LNAV/VNAV ALL CATS. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 1000-3, NA WHEN LOCAL WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 17, AMDT 3C. 2208221631-PERM