

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION TACAN OR VOR/DME STANDARD INSTRUMENT APPROACH PROCEDURE FLIGHT STANDARDS SERVICE - FAR PART 97.23										Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.									
TERMINAL ROUTES										MISSED APPROACH									
FROM		TO		COURSE AND DISTANCE				ALTITUDE		MAP: OBICE/1.78 DME									
SAV VORTAC GONYE/SAV 16.00 DME CW (IAF) EYOTA/16.00 DME (IF)		GONYE/16.00 DME		136.01 / 16.00				3000		CLIMB TO 4000 DIRECT SAV VORTAC AND VIA SAV R-000.82 TO TILLS INT/SAV 20.00 DME AND HOLD. ADDITIONAL FLIGHT DATA: HOLD N, RT, 180.82 INBOUND. CHART FAS OBST: 190 TOWER 320533N/0811100W CHART R-3005C, R-3005D. CHART VDP AT 3.02 DME; DISTANCE VDP TO THLD 1.25 MILES. CHART SAV R-136 AT GONYE. COCDA TO RW01: 2.98/74. FAC 213R OF RWY C/L EXTENDED 3000 FROM THLD.									
		EYOTA/16.00 DME		16.00 DME ARC				2500											
		FREMN/7.78 DME		006.16 / 8.22 (SAV R-186)				2000											
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT EYOTA/16.00 DME 3. FAC <u>006.16</u> FAF <u>FREMN/7.78 DME</u> DIST FAF TO MAP <u> </u> THLD <u>6.00</u> 4. MIN. ALT <u>EYOTA 2500, FREMN 2000</u> 8. MSA FROM: <u>SAV VORTAC 2600</u>										MAG VAR: 6W EPOCH YEAR: 2005									
MINIMUMS																			
TAKEOFF: ☐ STANDARD ☒ X		SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N/A		STANDARD @							
CATEGORY =====>		A			B			C			D			E					
		MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA	MDA	VIS	HAT/HAA			
S-1		500	5000	461	500	5000	461	500	6000	461	500	1 1/2	461	500	1 3/4	461			
CIRCLING		520	1	470	520	1	470	520	1 1/2	470	700	2	650	900	3	850			
NOTES: CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HILTON HEAD ISLAND, SC ALTIMETER SETTING AND INCREASE ALL MDA 80 FEET AND S-1 CATS C/D/E AND CIRCLING CAT D VISIBILITIES 1/4 MILE. CHART NOTE: VDP NA WHEN USING HILTON HEAD ISLAND ALTIMETER SETTING.																			
CITY AND STATE		ELEVATION: 50 TDZE: 39			FACILITY IDENTIFIER:			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP							
SAVANNAH, GA		AIRPORT NAME:			SAV			VOR/DME OR TACAN RWY 1, ORIG-C				AMDT ORIG-B							
		SAVANNAH/HILTON HEAD INTL						17 DEC 2009				DATE 07/02/2009							

