

**Federal Aviation
Administration**

Transmittal Letter 15-21

August 28, 2015

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
15-Oct-15	VA	Richmond	Richmond Executive-Chesterfield County	5/0093	08/06/15	RNAV (GPS) RWY 33, Orig-C

AIRAC Date: 15 October 2015

FDC 5/0093 FCI IAP RICHMOND EXECUTIVE-CHESTERFIELD COUNTY, RICHMOND, VA. RNAV (GPS) RWY 33, ORIG-C... LNAV/VNAV VIS 7/8 ALL CATS. CIRCLING CAT C MDA 760/HAA 524.. CHANGE LOCAL ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE RICHMOND INTL ALTIMETER SETTING AND INCREASE ALL DA 36 FEET AND ALL MDA 40 FEET; INCREASE LPV AND LNAV/VNAV ALL CATS AND LNAV CAT C/D AND CIRCLING CAT C VISIBILITY 1/8 MILE. CHANGE FOR INOPERATIVE MALSR NOTE TO READ: FOR INOPERATIVE MALSR, INCREASE LPV ALL CATS VISIBILITY TO 1 MILE AND LNAV CAT C/D TO 1 3/8 MILE. CHART NOTE: FOR INOPERATIVE MALSR WHEN USING RICHMOND INTL ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 1 1/8 MILE. THIS IS RNAV (GPS) RWY 33 ORIG-D. 1505121312-PERM