

**Federal Aviation
Administration**

Transmittal Letter 19-21

August 23, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/10/2019	WI	West Bend	West Bend Muni	9/4308	7/31/2019	RNAV (GPS) RWY 24, Orig-A

AIRAC Date: 10 OCTOBER 2019

FDC 9/4308 ETB IAP WEST BEND MUNI, West Bend, WI. RNAV (GPS) RWY 24, ORIG-A... DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 47C (116F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C OR ABOVE 47C. DELETE NOTE: NIGHT LANDING: RWY 6, 24 NA. DELETE PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT CYNDI VIA V7 NORTHBOUND. DELETE PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WOKNO VIA V7 SOUTHBOUND. DELETE NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. CHART NOTE: RWY 24 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: BARO-VNAV NA WHEN USING MILWAUKEE ALTIMETER SETTING. CHART NOTE: BARO-VNAV AND VDP NA WHEN USING LAWRENCE J TIMMERMAN ALTIMETER SETTING. CHART VDP AT 1.19 NM TO RW24*. DELETE NOTE: DME/DME RNP-0.3 NA. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MILWAUKEE ALTIMETER SETTING AND INCREASE ALL DA 64 FEET, ALL MDA 80 FEET, INCREASE LPV AND LNAV/VNAV VISIBILITY 1/4 MILE, LNAV CAT D VISIBILITY 1/4 MILE, CIRCLING CAT C/D VISIBILITY 1/4 MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE LAWRENCE J TIMMERMAN ALTIMETER SETTING: INCREASE LPV DA TO 1260 FEET, LNAV/VNAV DA TO 1433 FEET AND ALL VISIBILITIES 1/4 SM; INCREASE ALL MDAS 80 FEET AND VISIBILITY LNAV CAT D AND CIRCLING CAT C/D 1/4 SM. THIS IS RNAV (GPS) RWY 24, ORIG-B. 1908061529-PERM