

**Federal Aviation
Administration**

Transmittal Letter 21-21

August 20, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
10/7/2021	WI	West Bend	West Bend Muni	1/5341	8/12/2021	RNAV (GPS) RWY 24, Orig-B

AIRAC Date: 7 OCTOBER 2021

FDC 1/5341 ETB IAP WEST BEND MUNI, WEST BEND, WI. RNAV (GPS) RWY 24, ORIG-B...
CIRCLING CAT B MDA 1520/HAA 633, CAT C/D MDA 1560/HAA 673. CIRCLING CAT C
VISIBILITY 2, CAT D VISIBILITY 2 1/4. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER
SETTING NOT RECEIVED, USE MILWAUKEE/LAWRENCE J. TIMMERMAN ALTIMETER
SETTING AND INCREASE LPV DA TO 1260 FEET; LNAV/VNAV DA TO 1433 FEET AND ALL
VISIBILITY 1/4 SM; INCREASE ALL MDA 80 FEET AND LNAV CAT C/D AND CIRCLING CAT
C/D VISIBILITY 1/4 SM. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA
WHEN LOCAL WEATHER NOT AVAILABLE. DELETE PBN REQUIREMENTS NOTE: RNP
APCH. PBN REQUIREMENTS NOTE: RNP APCH-GPS. THIS IS RNAV (GPS) RWY 24, ORIG-
C. 2108111816-PERM