

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
CYNDI (IAF)	KEKSE (FB)	209.50 / 8.01	2500	LPV: DA LNAV/VNAV: DA LNAV: RW24 CLIMB TO 3000 DIRECT JEDEM AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SW, RT, 059.77 INBOUND. CHART FAS OBST: 1049 TREE 432651N/0880506W CHART FAS OBST: 1019 TREE 432556N/0880736W DISTANCE TO THLD FROM 312 HAT: 0.87 NM. WAAS CHANNEL # 70716 REFERENCE PATH ID: W24A
WOKNO (IAF)	KEKSE (FB)	293.23 / 5.80	2500	
KEKSE (IF)	FIVIX (FB)	240.08 / 6.10	2500	

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT KEKSE
3. FAC: 240.00 FAF: FIVIX DIST FAF TO MAP: 4.90 THLD: 4.90
4. MIN. ALT: KEKSE 2500, FIVIX 2500, ICUMU/2.50 NM TO RW24 1720*
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: 2500 GS ALT AT: FIVIX OM: MM: IM:
7. GS ANGLE: 3.00 TCH: 45.0 34:1 IS NOT CLEAR
8. MSA FROM: RW24 2900

MAG VAR: 1W

EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A	FOR THIS AIRPORT	ALTERNATE: N A			STANDARD @							
CATEGORY ==>		A			B			C			D			E		
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA		1196	1	312	1196	1	312	1196	1	312	1196	1	312			
LNAV/VNAV DA		1369	1 3/4	485	1369	1 3/4	485	1369	1 3/4	485	1369	1 3/4	485			
LNAV MDA		1300	1	416	1300	1	416	1300	1 1/4	416	1300	1 1/4	416			
CIRCLING		1420	1	533	1420	1	533	1460	1 1/2	573	1520	2	633			

NOTES:
 CHART NOTE: BARO-VNAV NA WHEN USING MILWAUKEE ALTIMETER SETTING.
 CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -16C (4F) OR ABOVE 47C (116F).
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA.
 SEE 8260-10

@ NA WHEN LOCAL WEATHER NOT AVAILABLE.

CITY AND STATE	ELEVATION: 887 TDZE: 884	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE:	SUP:
WEST BEND, WI	AIRPORT NAME: WEST BEND MUNI		RNAV (GPS) RWY 24, ORIG 08 APR 2010	AMDT: NONE
				DATED

QUALITY
&
CHECKED

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.**CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WOKNO VIA V7 SOUTHBOUND.****CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT CYNDI VIA V7 NORTHBOUND.*****LNAV ONLY****CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE MILWAUKEE ALTIMETER SETTING AND INCREASE ALL DA 64 FEET, ALL MDA 80 FEET, INCREASE LPV AND LNAV/VNAV VISIBILITY 1/4 MILE, LNAV CAT D VISIBILITY 1/4 MILE, CIRCLING CAT C/D VISIBILITY 1/4 MILE.**

CITY AND STATE

WEST BEND, WI

ELEVATION: 887 TDZE: 884

AIRPORT NAME:

WEST BEND MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 24, ORIG

08 APR 2010

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER KETB
RUNWAY RW24
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR 0
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W24A
LTP/FTP LATITUDE 432531.7200N
LTP/FTP LONGITUDE 0880718.0600W
LTP/FTP ELLIPSOIDAL HEIGHT +02316
FPAP LATITUDE 432445.7200N
FPAP LONGITUDE 0880902.7600W
THRESHOLD CROSSING HEIGHT (TCH) 00045.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1560
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 50.0

CRC REMAINDER

BF904AA0

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K5
LTP ORTHOMETRIC HEIGHT +02665
FPAP ORTHOMETRIC HEIGHT +02665

CITY AND STATE

WEST BEND, WI

ELEVATION: 887 TDZE: 884

AIRPORT NAME:

WEST BEND MUNI

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 24, ORIG

08 APR 2010

SUP:

AMDT: NONE

DATED:

QUALITY
CHECKED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP KETBK5FR24	ACYNDI	010CYNDIK5EA0E	A	IF					18000			A JS	
SUSAP KETBK5FR24	ACYNDI	020KEKSEK5EA0EE	B	010TF		20950080	+	02500				A JS	
SUSAP KETBK5FR24	AWOKNO	010WOKNOK5EA0E	A	IF					18000			A JS	
SUSAP KETBK5FR24	AWOKNO	020KEKSEK5EA0EE	B	010TF		29320058	+	02500				A JS	
SUSAP KETBK5FR24	R	010KEKSEK5EA0E	I	IF			+	02500	18000			A JS	
SUSAP KETBK5FR24	R	020FIVIXK5EA1E	F	051TF		24010061	+	02500			RW24	K5PGA	JS
SUSAP KETBK5FR24	R	020FIVIXK5EA2WALPV			ALNAV/VNAV	ALNAV							JS
SUSAP KETBK5FR24	R	021ICUMUK5EA0E	S	031TF		24000024	V	0172001721		-300		A JS	
SUSAP KETBK5FR24	R	030RW24	K5PGOGY	M	031TF	24000025		00919		-300		A JS	
SUSAP KETBK5FR24	R	040		0	M	010CA		2400	+	01196		A JS	
SUSAP KETBK5FR24	R	050JEDEMK5EA0EY		010DF				+	03000			A JS	
SUSAP KETBK5FR24	R	060JEDEMK5EA0EE		R020HM		05980040	+	03000				A JS	

[illegible]

SUP:	
AMDT:	NONE
DATED:	

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

	1	2	3	4	5	5	7	8	9	0	1	2	3
PP	123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KETBK5PR24 RW24 001 0000W24A0N4325317200W08807180600+023160300N4324457200W08809027600106751560000450F400500BF904AA0												
	SUSAP KETBK5PR24 RW24 002E +02665+02665LPV 70716												

	1	2	3	4	5	6	7	8	9	0	1	2	3
MSA	123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012												

	SUSAP KETBK5SRW24 K5PG 0 18018002925 M												

QUALITY
6
CHECKED

CITY AND STATE WEST BEND, WI	ELEVATION: 887 TDZE: 884 AIRPORT NAME: WEST BEND MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 24, ORIG 08 APR 2010	SUP:
				AMDT: NONE
				DATED: