

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW12
BAULK	NUBUE (FB)	099.73 / 14.69	3000	CLIMB TO 3000 DIRECT FALKN AND VIA 142.93 TRACK TO DAVIS AND HOLD.
MADDY	NUBUE (FB)	336.21 / 9.70	3000	
DALEY	MARKM (FB)	166.81 / 7.37	3000	
NUBUE (IAF)	ALOOF (FB)	031.23 / 5.00	3000	
MARKM (IAF)	ALOOF (FB)	211.31 / 5.00	3000	
ALOOF (IF)	IGOGY (FB)	121.27 / 6.12	2700	

This is a corrected copy of a procedure published in TL 09-09, dated 03.20.2009.

** this procedures corrects text quality issues in previous version. **

ADDITIONAL FLIGHT DATA:
HOLD SW, RT, 060.49 INBOUND.
CHART FAS OBST: 1229 TREE 423719N/0893708W
CHART VDP AT 1.06 MILES TO RW12.
IGOGY TO RW12: 3.04/40.

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT ALOOF
3. FAC: 121.35 FAF: IGOGY DIST FAF TO MAP: 4.88 THLD: 4.88
4. MIN. ALT: ALOOF 3000, IGOGY 2700
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: 34:1 IS CLEAR
8. MSA FROM: RW12 3600

MAG VAR: 0E EPOCH YEAR: 1985

MINIMUMS

TAKEOFF:		STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT			ALTERNATE: N A			STANDARD @						
CATEGORY =====>		A			B			C			D			E		
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA		1480	1	394	1480	1	394	1480	1	394	1480	1 1/4	394			
CIRCLING		1540	1	454	1640	1	554	1640	1 1/2	554	1640	2	554			

NOTES:
CHART NOTE: DME/DME RNP-0.3 NA. @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
CHART NOTE: VDP NA WHEN USING ALBERTUS ALTIMETER SETTING.
CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE ALBERTUS ALTIMETER SETTING AND INCREASE ALL MDA 100 FEET, INCREASE LNAV CAT C/D AND CIRCLING CAT C VISIBILITY 1/4 MILE.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT DALEY VIA V24-171 NORTHWEST BOUND.

CITY AND STATE	ELEVATION: 1086 TDZE: 1086	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 07 MAY 2009	SUP:
MONROE, WI	AIRPORT NAME: MONROE MUNI			AMDT: NONE
				DATED

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

CITY AND STATE MONROE, WI	ELEVATION: 1086 TDZE: 1086 AIRPORT NAME: MONROE MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 07 MAY 2009	SUP:
				AMDT: NONE
				DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

RUNWAY 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KEFTK5GRW12 0050001214 N42370762W089354858-0500 +0297401086000040075R

1 2 3 4 5 6 7 8 9 0 1 2 3
MSA 123456789012345678901234567890123456789012345678901234567890123456789012345678901234567890123456789012

SUSAP KEFTK5SRW12 K5PG 0 18018003625 M

CITY AND STATE

MONROE, WI

ELEVATION: 1086 TDZE: 1086

AIRPORT NAME:

MONROE MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 12, ORIG

07 MAY 2009

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC FLIGHT INSPECTION SUMMARY - VERSION 424-18 - RNAV (GPS)

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	BAULK	BAULK	010		IF		FB				
	BAULK	NUBUE	020	IAF	TF		FB	2.0	099.7 (100T)	014.7	03000
	BAULK	ALOOF	030		TF		FB	1.0	031.2 (031T)	005.0	03000
	DALEY	DALEY	010		IF		FB				
	DALEY	MARKM	020	IAF	TF		FB	2.0	166.8 (167T)	007.4	03000
	DALEY	ALOOF	030		TF		FB	1.0	211.3 (211T)	005.0	03000
	MADDY	MADDY	010		IF		FB				
	MADDY	NUBUE	020	IAF	TF		FB	2.0	336.2 (336T)	009.7	03000
	MADDY	ALOOF	030		TF		FB	1.0	031.2 (031T)	005.0	03000
		ALOOF	010	FACF	IF		FB				03000
		IGOGY	020	FAF	TF		FB	0.5	121.3 (121T)	006.1	02700
		RW12	030	MAP	TF		FO	0.3	121.4 (121T)	004.9	01126

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE
	FALKN	040		DF		FB	1.0			
	DAVIS	050		TF		FO	1.0	142.9 (143T)		03000
	DAVIS	060		HM	R	FO	2.0	060.5 (061T)	004.0	03000

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ALOOF	N424250.98	W0894832.66	N4242.850	W08948.544
	BAULK	N424105.09	W0901140.75	N4241.085	W09011.679
	DALEY	N425418.10	W0894718.24	N4254.302	W08947.304
	DAVIS	N422626.75	W0892303.09	N4226.446	W08923.052
	FALKN	N423533.73	W0893220.60	N4235.562	W08932.343
	IGOGY	N423940.01	W0894127.01	N4239.667	W08941.450
	MADDY	N422942.12	W0894645.65	N4229.702	W08946.761
	MARKM	N424707.42	W0894501.18	N4247.124	W08945.020
	NUBUE	N423834.43	W0895203.65	N4238.574	W08952.061
	RW12	N423707.62	W0893548.58	N4237.127	W08935.810

RUNWAY DATA	THRESHOLD	ELEVATION	TCH
RWY			
RW12	01086		40

CITY AND STATE MONROE, WI	ELEVATION: 1086 TDZE: 1086	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 12, ORIG 07 MAY 2009	SUP:
	AIRPORT NAME: MONROE MUNI			AMDT: NONE
				DATED: