

**Federal Aviation  
Administration**

**Transmittal Letter 20-15**

**May 29, 2020**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/16/2020	WV	Beckley	Raleigh County Memorial	0/1096	5/14/2020	RNAV (GPS) RWY 1, Amdt 1B

**AIRAC Date: 16 JULY 2020**

FDC 0/1096 BKW IAP RALEIGH COUNTY MEMORIAL, BECKLEY, WV. RNAV (GPS) RWY 1, AMDT 1B...  
CIRCLING CAT C MDA 3320/HAA 816, VIS 2 1/2, CAT D MDA 3500/HAA 996, VIS 3. CHANGE  
ALTIMETER SETTING NOTE TO READ: WHEN LOCAL ALTIMETER NOT RECEIVED, USE BLUEFIELD  
ALTIMETER SETTING AND INCREASE ALL DA 118 FEET AND ALL MDA 120 FEET; INCREASE LPV ALL  
CATS VISIBILITY 1/2 SM, LNAV/VNAV ALL CATS VISIBILITY 1/4 SM, LNAV CAT C/D VISIBILITY 1/2  
SM, AND CIRCLING CAT A/C VISIBILITY 1/4 SM. CHART CIRCLING ICON. ALTERNATE MINIMUMS:  
STANDARD. EXCEPT CAT C 900-2 1/2, CAT D 1000-3, NA WHEN LOCAL WEATHER NOT AVAILABLE.  
THIS IS RNAV (GPS) RWY 1, AMDT 1C. 2005141626-PERM