

**Federal Aviation
Administration**

Transmittal Letter 22-17

June 24, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
8/11/2022	MA	Hyannis	Cape Cod Gateway	2/8634	6/15/2022	RNAV (GPS) RWY 6, Orig-B

AIRAC Date: 11 AUGUST 2022

FDC 2/8634 HYA IAP CAPE COD GATEWAY, HYANNIS, MA. RNAV (GPS) RWY 6, ORIG-B... DELETE NOTE:
DME/DME RNP-0.3 NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. CHART NOTE: CIRCLING RWY 24 NA
AT NIGHT. CHART NOTE: RWY 6 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED.
CHANGE BACKUP ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE
CHATHAM ALTIMETER SETTING AND INCREASE LPV DA TO 348 FEET; INCREASE LNAV/VNAV DA TO 475
FEET AND INCREASE LNAV/VNAV ALL CATS VISIBILITY 1/8 SM; INCREASE ALL MDAS 40 FEET, LNAV
CATS C AND D VISIBILITY 1/8 SM; CIRCLING CATS C AND D VISIBILITY 1/4 SM. THIS IS RNAV (GPS) RWY 6,
ORIG-C. 2206141711-PERM