#### FEDERAL AVIATION ADMINISTRATION

# FLIGHT STANDARDS SERVICE

# RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE

## **TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

AIRPORT ID KIKV	PROCEDURE NAME RNAV (GPS) RWY 22	<u>ORIGINAL/AMENDMEN</u> 1A	<u>I</u> <u>CIT</u> ANKE		STATE IA	
AIRPORT ELEVATION 910	<b>TDZE</b> 902	<u>SUPERSEDED</u> RNAV (GPS) RWY 22	ORIGINAL/AMENDMENT 1	<b>DATED</b> 01/05/2017	MAG VAR 3E	EPOCH YEAR 2000

FACILITY COORDINATES OF FACILITIES ACTUAL EFFECTIVE DATE ROUTINE

RNAV

ROUTINE

REQUIRED EFFECTIVE DATE CANCEL/SUSPEND
ROUTINE

TAA

FROM	FIX TYPE	TO	FIX TYPE	ALTITUDE
1. 132/30 CW 312/30	NOPT	ZUNIP	IF/IAF	3200
2. 312/30 CW 132/30		ZUNIP	IF/IAF	4000

#### **TERMINAL ROUTES**

FROM	FIX TYPE	<u>10</u>	FIX TYPE	LEG TYPE	FO/FB	RNP	<u>COURSE</u>	DISTANCE	ALTITUDE
ZUNIP	IF/IAF	CABOX		TF	FB	1.00	222.11	5.00	2500
CABOX	FAF	JONRU/2.50 NM TO RW22		TF	FB	0.30	222.06	2.38	
JONRU/2.50 NM TO RW22		RW22	MAP	TF	FO	0.30	222.06	2.50	
RW22	MAP	1500 MSL		CA			222.06		1500
1500 MSL		ZUNIP		DF	FO	1.00			3200

#### MISSED APPROACH

MAP:

LNAV: RW22

#### **MISSED APPROACH INSTRUCTIONS:**

(DO NOT EXCEED 240 KIAS UNTIL ZUNIP) CLIMB TO 1500 THEN CLIMBING RIGHT TURN TO 3200 DIRECT ZUNIP AND HOLD.

#### **ALTERNATE MISSED APPROACH INSTRUCTIONS:**

<u>AIRPORT ID</u> KIKV		JRE NAME S) RWY 22		ORIGINAL/AMENDMENT 1A	<u>CITY</u> ANKENY	<u>STATE</u> IA	
PROFILE:							
1. PT SIDE OF COURSE	OUTE	BOUND	FT WITHIN	MILES OF	(IAF)		
2. HOLD NE ZUNIP, RT, 222.11 IN	BOUND, 3200 FT. IN LIEU O	F PT (IAF), MA	X 6000.				
<b>3. FAC:</b> 222.06	FAF: CABOX		DIST FA	F TO MAP: 4.88	DIST FAF TO THLD: 4.88		
4. MIN ALT: ZUNIP 3200, CABO	OX 2500, JONRU/2.50 NM T	O RW22 1740					
5. DIST TO THLD FROM FAF:	MM:	IM:	150 HAT:	GS ANT:			
6. MIN GP INCPT:	GP ALT AT FAF :			OM:	MM:	IM:	
7. GP ANGLE:	34:1: IS NOT CLEAR	20:1: IS CL	EAR <b>TCH</b>	:			
8. MSA FROM:							

#### **PBN REQUIREMENTS NOTE:**

RNP APCH - GPS.

### NOTES:

CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).

#### **ADDITIONAL FLIGHT DATA:**

CHART FAS OBST: 1110 TREE 414346N/0933159W. CHART 1136 TANK (19-044680) 414401N/0933146W. CHART VDP AT 1.33 NM TO RW22.

CHART CIRCLING ICON. CABOX TO RW22: 3.00/45.

#### MINIMUMS:

TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

**ALTERNATE: NA** STANDARD - CAT D 900-2 3/4

CATEGORY:		Α			В			С			D			E	
FINAL TYPE	DA/MDA	<u>VIS</u>	HAT/HAA												
LNAV MDA	1360	1	458	1360	1	458	1360	1 3/8	458	1360	1 3/8	458			
CIRCLING	1560	1	650	1560	1	650	1560	1 3/4	650	1760	2 3/4	850			



AIRPORT IDPROCEDURE NAMEORIGINAL/AMENDMENTCITYSTATEKIKVRNAV (GPS) RWY 221AANKENYIA

#### **CHANGES - REASONS**

- 1. ADDED "MAX 6000" TO HOLD-IN-LIEU ON LINE 2 IAW 8260.19I PARA 8-6-7.B.(2).
- 2. ADDED "20:1 IS CLEAR" TO LINE 7 THERE ARE NO 20:1 PENETRATIONS TO RWY 22.
- 3. ADDED PBN REQUIREMENTS NOTE: "RNP APCH GPS" IAW 8260.19I 8-6-8.B.(2).
- 4. REMOVED DME/DME RNP -0.3 NA NO LONGER REQUIRED.

AOPA 🔽

- 5. CHANGED CHART NOTE FROM "CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED" TO "CHART NOTE: RWY 22 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED" 20:1 PENETRATIONS NO LONGER EXIST HOWEVER 34:1 IS STILL NOT CLEAR FOR RWY 22.
- 6. REMOVED "CHART NOTE: STRAIGHT-IN RWY 22 NA AT NIGHT" RWY 22 20:1 PENETRATIONS NO LONGER EXIST.

APA | HAI |

- 7. UPDATED ADDITIONAL FLIGHT DATA NOTE FROM "CHART 1136 SILO 414401N/0933146W" TO "CHART 1136 TANK (19-044680) 414401N/0933146W" SAME OBSTACLE, TYPE UPDATED, ID ADDED IAW 8260.19I 8-6-10.C.
- 8. ADDED "CHART VDP AT 1.33 NM TO RW22" TO ADDITIONAL FLIGHT DATA VDP PUBLISHABLE DUE TO REMOVAL OF 20:1 PENETRATIONS.

NRAA 🔽

JASON KRETSCHMER Jul 15, 2021

9. REMOVED "1290 AAO 414554N/0933006W" FROM ADDITIONAL FLIGHT DATA - AAO PLANT WAS 100 FT HIGHER THAT NECESSARY ACCORDING TO THE MAP STUDY AND THEREFORE AN INVALID 7:1 OBSTACLE FOR THAT SEGMENT OF THE APPROACH.

OTHER: 7ALL DSM ATCT AMGR

COO	RDIN.	ATED V	VITH:
ΔΔΔ	П	ΔΙ ΡΔ	

FLIGHT CHECKED BY PROCESSED IAW AIRCRAFT OPERATIONS GROFLIGHT INSPECTION REVIEW NOT REQUIRED	DUP (AJF-10) MEMO, APRIL 29, 2020, SUBJECT:	,	signed by DATE RETSCHMER	
DEVELOPED BY JASON KRETSCHMER (COLIN CAMPBELL)	Digitally signed by  JASON KRETSCHMER	OFFICE AJV-A421	5, 2021 <b>DATE</b> 04/25/2021	
APPROVED BY	Jul 15, 2021	<u>OFFICE</u>	DATE	TITLE
MARLON ROBINSON	Digitally signed by	AJV-A420		MANAGER

OVALITY 16 CHECKEP