

**Federal Aviation
Administration**

Transmittal Letter 26-16

June 5, 2026

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/9/2026	NY	Batavia	Genesee County	6/3145	3/25/2026	ILS OR LOC RWY 28, Amdt 6C

AIRAC Date: 9 JULY 2026

FDC 6/3145 GVQ IAP GENESEE COUNTY, BATAVIA, NY. ILS OR LOC RWY 28, AMDT 6C...
S-LOC 28 CAT C VISIBILITY 5/8. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL
ALTIMETER SETTING NOT RECEIVED, USE ROC ALTIMETER SETTING: INCREASE S-ILS
28 DA TO 1213 FEET; INCREASE ALL MDAS 120 FEET AND S-LOC 28 VISIBILITY CAT C 3/8
SM, S-LOC 28 VISIBILITY CAT D 1/4 SM, AND CIRCLING VISIBILITY CATS C/D 1/2 SM.
CHANGE ALTERNATE MINIMUMS TO READ: ILS: STANDARD - NA WHEN LOCAL WEATHER
NOT AVAILABLE; LOC: STANDARD - CAT C 900-2 1/4, CAT D 900-2 1/2, NA WHEN LOCAL
WEATHER NOT AVAILABLE. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 28
CATS C/D VISIBILITY TO 1 SM. THIS IS ILS OR LOC RWY 28, AMDT 6D. 2603241946-PERM