

**Federal Aviation
Administration**

Transmittal Letter 23-03

December 9, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
1/26/2023	FL	New Smyrna Beach	New Smyrna Beach Muni	2/6973	11/29/2022	RNAV (GPS) RWY 7, Orig-B

AIRAC Date: 26 JANUARY 2023

FDC 2/6973 EVB IAP NEW SMYRNA BEACH MUNI, NEW SMYRNA BEACH, FL. RNAV (GPS) RWY 7, ORIG-B... CHANGE NOTE TO READ: RWY 7 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. CHANGE NOTE TO READ: STRAIGHT-IN RWY 7 NA AT NIGHT, CIRCLING RWY 7, 11, 25 NA AT NIGHT. DELETE NOTE: VDP NA WHEN USING DAYTONA BEACH ALTIMETER SETTING. CHANGE PBN REQUIREMENTS NOTE TO READ: RNP APCH-GPS. DELETE VDP 1.4NM TO RW07. LNAV VIS CAT D 1 3/8. CIRCLING VIS CAT C 1 3/4, CAT D 2. CHANGE NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE DAYTONA BEACH ALTIMETER SETTING AND INCREASE ALL MDAS 40 FEET, LNAV VISIBILITY CAT C/D 1/8 SM, AND CIRCLING VISIBILITY CAT C/D 1/4 SM. ALTERNATE MINIMUMS: STANDARD, NA WHEN LOCAL WEATHER NOT AVAILABLE. CHANGE PLANVIEW NOTE TO READ: PROCEDURE NA FOR ARRIVALS AT KIZER ON T210-347-353 AND V257 SOUTHBOUND, V152-437 SOUTHWEST BOUND AND V437 NORTHWEST BOUND. CHANGE PLANVIEW NOTE TO READ: PROCEDURE NA FOR ARRIVALS AT OAKIE ON T208 AND V3-533 SOUTHBOUND, AND V533 NORTHEAST BOUND. THIS IS RNAV (GPS) RWY 7, ORIG-C. 2211281732-PERM