

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
ILS STANDARD INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.29**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT</u> SOUTHWEST GEORGIA RGNL	<u>AIRPORT ID</u> KABY	<u>PROCEDURE NAME</u> ILS OR LOC RWY 5	<u>ORIGINAL/AMENDMENT</u> 13B	<u>CITY</u> ALBANY	<u>STATE</u> GA	
<u>AIRPORT ELEVATION</u> 196	<u>TDZE</u> 196	<u>SUPERSEDED</u> ILS OR LOC RWY 4	<u>ORIGINAL/AMENDMENT</u> 13A	<u>DATED</u> 09/13/2018	<u>MAG VAR</u> 5W	<u>EPOCH YEAR</u> 2020
<u>FACILITY</u> I-ABY	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 26 MARCH 2020	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

TERMINAL ROUTES

<u>FROM</u>	<u>FIX TYPE</u>	<u>TO</u>	<u>FIX TYPE</u>	<u>LEG TYPE</u>	<u>FO/FB</u>	<u>RNP</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>ALTITUDE</u>
PZD VOR/DME		FOLKA INT/I-ABY 7.37 DME					178.68	12.07	2200
SALER		FOLKA INT/I-ABY 7.37 DME		TF	FO	1.00	319.14	9.37	2200
ELMOE		FOLKA INT/I-ABY 7.37 DME		TF	FO	1.00	016.78	10.31	2200
AYUVO/PZD 17.01 DME CCW	IAF	HAVEX/I-ABY 13.55 DME	NOPT				17.01 DME ARC (PZD LR-201)		2200
HAVEX/I-ABY 13.55 DME	IF	FOLKA INT/I-ABY 7.37 DME	PFAF				047.10	6.19 (I-ABY)	2200

MISSED APPROACH

MAP:

ILS: DA
LOC: 6.11 NM AFTER FOLKA INT/I-ABY 7.37 DME OR AT I-ABY 1.26 DME

MISSED APPROACH INSTRUCTIONS:

CLIMB TO 1000 THEN CLIMBING LEFT TURN TO 3000 DIRECT PZD VOR/DME AND HOLD.

ALTERNATE MISSED APPROACH INSTRUCTIONS:

PROFILE:

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. HOLD SW FOLKA, RT, 047.10 INBOUND, 2200 FT. IN LIEU OF PT (IAF), MAX 4600.
3. FAC: 047.10 PFAF: FOLKA INT/I-ABY 7.37 DME DIST PFAF TO MAP: 6.11 DIST PFAF TO THLD: 6.11
4. MIN ALT: FOLKA INT/I-ABY 7.37 DME 2200, XIKHO/I-ABY 2.66 DME 680*
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: GS ANT: 1150
6. MIN GS INCPT: 2200 GS ALT AT PFAF : FOLKA INT/I-ABY 7.37 DME 2200 OM: MM: IM:
7. GP ANGLE: 3.00 34:1: 20:1: TCH: 59.6
8. MSA FROM: PZD VOR/DME 2600



EQUIPMENT REQUIREMENTS NOTES:

PBN REQUIREMENTS NOTE: FROM ELMOE AND SALER: RNAV-1 GPS REQUIRED.

NOTES:

CHART PROFILE NOTE: VGSI AND ILS GLIDEPATH NOT COINCIDENT (VGSI ANGLE {ANGLE}/TCH {FEET}).
*LOC ONLY
CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-LOC 5 CATS C/D VISIBILITY TO 1 3/8 SM AND XIKHO FIX MINIMUMS S-LOC 5 CATS C/D VISIBILITY TO RVR 5500.

ADDITIONAL FLIGHT DATA:

CHART CIRCLING ICON.
CHART PZD R-295 AT AYUVO.
FAS OBST: 309 TREES 313034N/0841332W.
HOLD NW, RT, 145.00 INBOUND

MINIMUMS:
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT

ALTERNATE: NA ☐ ILS: STANDARD - NA WHEN CONTROL TOWER CLOSED.; LOC: STANDARD - CAT C 800-2 1/4, CAT D 800-2 1/2, NA WHEN CONTROL TOWER CLOSED.

CATEGORY:	A			B			C			D			E		
FINAL TYPE	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA	DA/MDA	VIS	HAT/HAA
S-ILS 05	396	2400	200	396	2400	200	396	2400	200	396	2400	200			
S-LOC 05	680	2400	484	680	2400	484	680	5000	484	680	5000	484			
CIRCLING	680	1	484	680	1	484	940	2 1/4	744	940	2 1/2	744			
XIKHO FIX MINIMUMS (DME REQUIRED)															
S-LOC 05	560	2400	364	560	2400	364	560	3500	364	560	3500	364			
CIRCLING	640	1	444	660	1	464	940	2 1/4	744	940	2 1/2	744			

CHANGES - REASONS

1. CHANGED ALL REFERENCES FROM RWY 4/22 TO RWY 5/23. DUE TO RUNWAY NUMBERING CHANGE FOR MAGVAR PER AIRPORT MANAGER AND FPT.

COORDINATED WITH:

A4A ☒ ALPA ☒ AOPA ☒ APA ☒ HAI ☐ NBAA ☒ OTHER: ZJX, ABY ATCT, AMGR

FLIGHT CHECKED BY
PROCESSED IAW AIRCRAFT OPERATIONS GROUP (AJW-33) MEMO, OCTOBER 3, 2018, SUBJECT:
FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE

DATE
Digitally signed by
MARK D ADAMS
Nov 15, 2019

DEVELOPED BY
GEORGE H. TRAMMELL

Digitally signed by
GEORGE H TRAMMELL
Oct 18, 2019

OFFICE
AJV-A412

DATE
08/28/2019

APPROVED BY
JULIE MORGAN

Digitally signed by
MARK D ADAMS
Nov 15, 2019

OFFICE
AJV-A410

DATE

TITLE
MANAGER

