

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE
GALLS	RIPEE (TF) (FO) (RNP 2.00)	053.18 / 9.48	4000
RIPEE (IF/IAF)	TIKKU (TF) (FB) (RNP 1.00)	268.01 / 6.09	2900
TIKKU (FAF)	RW27 (MAP) (TF) (FO) (RNP 0.30)	267.93 / 5.59	
RW27 (MAP)	1469 MSL (CA)	267.93	
1469 MSL	ZUNKO (DF) (FO) (RNP 1.00)		4000

LNAV: RW27

CLIMB TO 4000 DIRECT ZUNKO AND HOLD.

**ADDITIONAL FLIGHT DATA:
HOLD W, RT, 087.68 INBOUND.
CHART FAS OBST: 1730 TOWER 395444N/0800208W
CHART PROFILE NOTE: VISUAL SEGMENT - OBSTACLES.**

1. PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. **HOLD E RIPEE, RT, 268.01 INBOUND, 4000 FT. IN LIEU OF PT (IAF)**
3. FAC: 267.93 FAF: TIKKU DIST FAF TO MAP: 5.59 THLD: 5.59
4. MIN. ALT: **RIPEE 4000, TIKKU 2900**
5. DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
6. MIN GS INCPT: GS ALT AT: OM: MM: IM:
7. GS ANGLE: TCH: **34:1 IS NOT CLEAR**
8. MSA FROM: **RW27 4200**

MAG VAR: **9W** EPOCH YEAR: **2010**

MINIMUMS

TAKEOFF: <u> </u> SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N <input type="checkbox"/> A <input checked="" type="checkbox"/> X <input type="checkbox"/>														
CATEGORY >>>>>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LNAV MDA	2100	1 1/4	1031	2100	1 1/2	1031	2100	3	1031		NA				
CIRCLING	2100	1 1/4	1031	2140	1 1/2	1071	2140	3	1071		NA				

NOTES:
 CHART NOTE: NIGHT LANDING: RWY 27 NA.
 CHART NOTE: RWY 27 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: USE WASHINGTON ALTIMETER SETTING, WHEN NOT RECEIVED USE MORGANTOWN ALTIMETER SETTING AND
 (CONTINUED ON PAGE 2)



CITY AND STATE WAYNESBURG, PA	ELEVATION: 1069 TDZE: 1069 AIRPORT NAME: GREENE COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, ORIG-A 22 JUNE 2017	SUP: AMDT: ORIG DATED 06/05/2008
---	---	-------------------------------------	--	--

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDAS 20 FEET.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT GALLS VIA V119 W BOUND AND V8-92-214 W BOUND.



CITY AND STATE WAYNESBURG, PA	ELEVATION: 1069 TDZE: 1069 AIRPORT NAME: GREENE COUNTY	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 27, ORIG-A 22 JUNE 2017	SUP:
				AMDT: ORIG
				DATED: 06/05/2008