

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOKES	SEVEN	YOKES7.YOKES	SIX	07/11/2018	30 JAN 2020
<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
☐	☐	☒	☐	☐	☒

DP ROUTE DESCRIPTION:
DENVER INTL:

THIS IS A CORRECTED COPY PREVIOUSLY PUBLISHED IN NFDD 238.

TAKEOFF RWY 8: CLIMB ON HEADING 082.53 TO INTERCEPT COURSE 065.90 TO CROSS LASSS AT OR BELOW 10000, THEN ON TRACK 024.35 TO SPYCE, THEN ON TRACK 353.50 TO TURBN, THEN ON TRACK 315.84 TO CROSS CHICN AT OR ABOVE 14000, THEN ON TRACK 355.36 TO CROSS KKIMM AT OR ABOVE 16000, THEN ON TRACK 028.48 TO BTEN, THEN ON TRACK 028.21 TO YOKES, THENCE ...

TAKEOFF RWY 16L: CLIMB ON HEADING 172.51 TO 5934, THEN RIGHT TURN DIRECT TO CROSS MUGBE AT OR BELOW 10000, THEN ON TRACK 319.96 TO WAZEE, THEN ON TRACK 354.86 TO LODOE, THEN ON TRACK 029.62 TO CROSS RINKR AT OR ABOVE 14000, THEN ON TRACK 041.10 TO CROSS ELCEE AT OR ABOVE 16000, THEN ON TRACK 042.18 TO YOKES, THENCE ...

TAKEOFF RWY 16R: CLIMB ON HEADING 172.51 TO 5934, THEN RIGHT TURN DIRECT TO CROSS MUGBE AT OR BELOW 10000, THEN ON TRACK 319.96 TO WAZEE, THEN ON TRACK 354.86 TO LODOE, THEN ON TRACK 029.62 TO CROSS RINKR AT OR ABOVE 14000, THEN ON TRACK 041.10 TO CROSS ELCEE AT OR ABOVE 16000, THEN ON TRACK 042.18 TO YOKES, THENCE ...

TAKEOFF RWY 17L: CLIMB ON HEADING 172.54 TO INTERCEPT COURSE 125.30 TO CROSS GISTT AT OR ABOVE 7000 AND AT/BELOW 250 KIAS, THEN ON TRACK 065.00 TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 355.43 TO CROSS GINTH AT OR BELOW 11000, THEN ON TRACK 355.43 TO SPYCE, THEN ON TRACK 353.50 TO TURBN, THEN ON TRACK 315.84 TO CROSS CHICN AT OR ABOVE 14000, THEN ON TRACK 355.36 TO CROSS KKIMM AT OR ABOVE 16000, THEN ON TRACK 028.48 TO BTEN, THEN ON TRACK 028.21 TO YOKES, THENCE ...

TAKEOFF RWY 17R: CLIMB ON HEADING 172.53 TO INTERCEPT COURSE 118.50 TO CROSS GISTT AT OR ABOVE 7000 AND AT/BELOW 250 KIAS, THEN ON TRACK 065.00 TO CROSS KIDNG AT OR BELOW 10000, THEN ON TRACK 355.43 TO CROSS GINTH AT OR BELOW 11000, THEN ON TRACK 355.43 TO SPYCE, THEN ON TRACK 353.50 TO TURBN, THEN ON TRACK 315.84 TO CROSS CHICN AT OR ABOVE 14000, THEN ON TRACK 355.36 TO CROSS KKIMM AT OR ABOVE 16000, THEN ON TRACK 028.48 TO BTEN, THEN ON TRACK 028.21 TO YOKES, THENCE ...

TAKEOFF RWY 25: CLIMB ON HEADING 262.51 TO INTERCEPT COURSE 294.01 TO CROSS MUGBE AT OR BELOW 10000, THEN ON TRACK 319.96 TO WAZEE, THEN ON TRACK 354.86 TO LODOE, THEN ON TRACK 029.62 TO CROSS RINKR AT OR ABOVE 14000, THEN ON TRACK 041.10 TO CROSS ELCEE AT OR ABOVE 16000, THEN ON TRACK 042.18 TO YOKES, THENCE ...

TAKEOFF RWY 34L: CLIMB ON HEADING 352.51 TO INTERCEPT COURSE 024.83 TO CROSS IRIIS AT OR BELOW 10000, THEN ON TRACK 018.72 TO CROSS VELAA AT OR ABOVE 12000, THEN ON TRACK 018.80 TO YOKES, THENCE ...

TAKEOFF RWY 34R: CLIMB ON HEADING 352.51 TO INTERCEPT COURSE 022.84 TO CROSS IRIIS AT OR BELOW 10000, THEN ON TRACK 018.72 TO CROSS VELAA AT OR ABOVE 12000, THEN ON TRACK 018.80 TO YOKES, THENCE ...

TAKEOFF RWY 35L: CLIMB ON HEADING 352.53 TO INTERCEPT COURSE 011.45 TO CROSS IRIIS AT OR BELOW 10000, THEN ON TRACK 018.72 TO CROSS VELAA AT OR ABOVE 12000, THEN ON TRACK 018.80 TO YOKES, THENCE ...

TAKEOFF RWY 35R: CLIMB ON HEADING 352.54 TO INTERCEPT COURSE 006.97 TO CROSS IRIIS AT OR BELOW 10000, THEN ON TRACK 018.72 TO CROSS VELAA AT OR ABOVE 12000, THEN ON TRACK 018.80 TO YOKES, THENCE ...

...THEN AS DEPICTED, MAINTAIN FL230 OR FILED LOWER ALTITUDE. EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

CENTENNIAL:

TAKEOFF RWY 17L, 17R: CLIMB ON HEADING 169.95 TO 6400, THEN CONTINUE CLIMB ON HEADING 169.95 OR AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 35L, 35R: CLIMB ON HEADING 349.95 TO 6400, THEN CONTINUE CLIMB ON HEADING 349.95 OR AS ASSIGNED BY ATC, THENCE ...

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOKES	SEVEN	YOKES7.YOKES	SIX	07/11/2018	30 JAN 2020

... RADAR VECTORS TO VELAA, THEN AS DEPICTED. MAINTAIN FL230 OR FILED LOWER ALTITUDE. EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

ROCKY MOUNTAIN METROPOLITAN:

TAKEOFF RWY 12L, 12R: CLIMB ON HEADING BETWEEN 150 CCW 350 AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 30L, 30R: CLIMBING RIGHT TURN HEADING BETWEEN 350 CW 113 AS ASSIGNED BY ATC, THENCE ...

... RADAR VECTORS TO VELAA, THEN AS DEPICTED. MAINTAIN FL230 OR FILED LOWER ALTITUDE. EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

NORTHERN COLORADO RGNL:

TAKEOFF RWY 15: CLIMB ON HEADING BETWEEN 180 CCW 350 AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 33: CLIMBING RIGHT TURN TO HEADING BETWEEN 350 CW 150 AS ASSIGNED BY ATC, THENCE ...

... RADAR VECTORS TO VELAA, THEN AS DEPICTED. MAINTAIN FL230 OR FILED LOWER ALTITUDE. EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

COLORADO AIR AND SPACE PORT:

TAKEOFF RWY 8: CLIMB ON HEADING 083.15 TO 6020, THEN CONTINUE CLIMB ON HEADING 083.15 OR AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 17: CLIMB ON HEADING 171.99 TO 6020, THEN CONTINUE CLIMB ON HEADING 171.99 OR AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 26: CLIMB ON HEADING 263.17 TO 6020, THEN CONTINUE CLIMB ON HEADING 263.17 OR AS ASSIGNED BY ATC, THENCE ...

TAKEOFF RWY 35: CLIMB ON HEADING 351.99 TO 6020, THEN CONTINUE CLIMB ON HEADING 351.99 OR AS ASSIGNED BY ATC, THENCE ...

... RADAR VECTORS TO VELAA, THEN AS DEPICTED. MAINTAIN FL230 OR FILED LOWER ALTITUDE. EXPECT HIGHER FILED ALTITUDE 10 MINUTES AFTER DEPARTURE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
SCOTTSBLUFF	YOKES7.BFF	YOKES	COPLA	015.15	16.37			
		COPLA	BFF	015.25	69.70			
CHICI	YOKES7.CHICI	YOKES	CHICI	036.15	69.00			

PROCEDURAL DATA NOTES:

NOTE: DME/DME/IRU OR GPS REQUIRED.

NOTE: RNAV 1

NOTE: TURBOJETS ONLY.

NOTE: ACCELERATE TO AT OR ABOVE 250 KIAS ABOVE 10000. IF SLOWER SPEED IS REQUIRED TO MEET CROSSING RESTRICTIONS ADVISE CLNC DEL PRIOR TO TAXI.

NOTE: DENVER INTL - TAKEOFF RWY 8, 16L, 16R, 17L, 17R, 25, 34L, 34R, 35L, 35R - RADAR REQUIRED FOR NON-GPS EQUIPPED AIRCRAFT.

NOTE: CENTENNIAL, ROCKY MOUNTAIN METROPOLITAN, NORTHERN COLORADO RGNL AND COLORADO AIR AND SPACE PORT AIRPORT - RADAR REQUIRED.

TAKEOFF MINIMUMS:

DENVER INTL:

RWY 7, 26: NA - ATC



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

DP NAME	NUMBER	DP COMPUTER CODE	SUPERSEDED NUMBER	DATED	EFFECTIVE DATE
YOKES	SEVEN	YOKES7.YOKES	SIX	07/11/2018	30 JAN 2020

RWY 8: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 8000, THEN 285 FT PER NM TO 16000.
RWY 16L: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 260 FT PER NM TO 16000.
RWY 16R: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 260 FT PER NM TO 16000.
RWY 17L: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 220 FT PER NM TO 15000.
RWY 17R: STANDARD WITH MINIMUM CLIMB OF 455 FT PER NM TO 6500, THEN 220 FT PER NM TO 15000.
RWY 25: STANDARD WITH MINIMUM CLIMB OF 425 FT PER NM TO 8000, THEN 270 FT PER NM TO 15000
RWY 34L: STANDARD WITH MINIMUM CLIMB OF 465 FT PER NM TO 7000, THEN 240 FT PER NM TO 12000.
RWY 34R: STANDARD WITH MINIMUM CLIMB OF 465 FT PER NM TO 7000, THEN 240 FT PER NM TO 12000.
RWY 35L: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 250 FT PER NM TO 12000.
RWY 35R: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 7000, THEN 250 FT PER NM TO 12000.

CENTENNIAL:

RWY 10, 28: NA - ATC
RWY 35L, 35R: STANDARD.
RWY 17L: STANDARD WITH MINIMUM CLIMB OF 255 FT PER NM TO 8000.
RWY 17R: STANDARD WITH MINIMUM CLIMB OF 370 FT PER NM TO 8000.

ROCKY MOUNTAIN METROPOLITAN:

RWY 3, 21: NA - ATC.
RWY 12L, 12R, 30L, 30R: STANDARD.

NORTHERN COLORADO RGNL:

RWY 6, 24: NA - VFR RUNWAY.
RWY 15, 33: STANDARD WITH MINIMUM CLIMB OF 400 FT PER NM TO 8000.

COLORADO AIR AND SPACE PORT:

RWY 8, 17, 26, 35: STANDARD.

TAKEOFF OBSTACLES NOTES:

DENVER INTL:
 SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

ROCKY MOUNTAIN METROPOLITAN:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CENTENNIAL:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

NORTHERN COLORADO RGNL:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

COLORADO AIR AND SPACE PORT:

SEE FORM 8260-15A, TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP).

CONTROLLING OBSTACLES:

CENTENNIAL:
RWY 17L: 6559 FT MSL AAO 392953.93N/1045044.26W.
RWY 17R: 6021 FT MSL OBS LT ON BLDG 393302.52N/1045119.43W, 6559 FT MSL AAO 392953.93N/1045044.26W.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOKES	SEVEN	YOKES7.YOKES	SIX	07/11/2018	30 JAN 2020

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KDEN 8E EPOCH YR: 2015.
DME/DME ASSESSMENT: SAT (RNP 2.0).
ALL AIRPORTS - CHART: TOP ALTITUDE: FL230.
CHART SPEED ICON MAXIMUM SPEED 250 KIAS AT GISTT

PILOT NAVIGATION AREA:

10 NM ARC CENTERED ON VELAA (IF), CW
FROM: POINT A (BEARING 351 DEGREES TO VELAA)
TO: POINT B (BEARING 047 TO VELAA)
MINIMUM ALTITUDE - 12000

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
DENVER INTL (KDEN)	DENVER	CO
CENTENNIAL (KAPA)	DENVER	CO
ROCKY MOUNTAIN METROPOLITAN (KBJC)	DENVER	CO
NORTHERN COLORADO RGNL (KFNL)	FORT COLLINS/LOVELAND	CO
COLORADO AIR AND SPACE PORT (KCFO)	DENVER	CO

COMMUNICATIONS:

DENVER INTL: D-ATIS DEP, CLNC DEL, CPDLC, DEN DEP CON.
CENTENNIAL: ATIS, CLNC DEL, DEN DEP CON.
ROCKY MOUNTAIN METROPOLITAN: ATIS, CLNC DEL, DEN DEP CON.
NORTHERN COLORADO RGNL: DEN DEP CON.
COLORADO AIR AND SPACE PORT: ATIS, CLNC DEL, DEN DEP CON, DEN CLNC DEL (WHEN TOWER CLOSED).

FIXES AND/OR NAVAIDS:

REMARKS:

ABBREVIATED AMENDMENT

CLIMB GRADIENTS AT CENTENNIAL OFF RWY 17L/R ARE OBSTACLE DRIVEN WITH THE CLIMB TO ALTITUDE DETERMINED BY LOCATION OF 8000 MVA AND PROXIMITY TO HIGHER MVA'S.

DENVER INTL CLIMB GRADIENTS ARE FOR FMS ENGAGEMENT AT SPECIFIC LOCATIONS, FOR TRANSITON CROSSING ALTITUDES.

THE AIRLINE INDUSTRY HAS REQUESTED THAT BLOCK ALTITUDES NOT BE PUBLISHED ON THE PROCEDURE, WAIVER ON FILE TO REMOVE AT OR ABOVE ALTITUDES ASSOCIATED WITH CROSS AT OR BELOW ALTITUDES.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOKES	SEVEN	YOKES7.YOKES	SIX	07/11/2018	30 JAN 2020

ATC HAS REQUESTED TO DEVIATE FROM THE STANDARD NAMING CONVENTION CONTAINED IN FAAO 8260.46. SID NAMES CORRESPOND WITH WAYPOINT NAMES AT OUTER BOUNDARY OF DENVER TRACON/ARTCC AIRSPACE. WAIVER APPROVED AND ON FILE.

KDEN RWY 8: FLIGHT TRACK DISTANCE TO YOKES PNA BOUNDARY 55 NM PER ATC.
KAPA RWY 17L, 17R: FLIGHT TRACK DISTANCE TO YOKES PNA BOUNDARY 42 NM PER ATC.
KAPA RWY 35L, 35R: FLIGHT TRACK DISTANCE TO YOKES PNA BOUNDARY 44 NM PER ATC.
KBJC RWY 12L, 12R, 30L, 30R: FLIGHT TRACK DISTANCE TO YOKES PNA BOUNDARY 33 NM PER ATC.
KFNL RWY 15, 33: FLIGHT TRACK DISTANCE TO YOKES PNA BOUNDARY 58 NM PER ATC.
KCFO RWY 8, 17, 26, 35: FLIGHT TRACK DISTANCE TO YOKES PNA BOUNDARY 64 NM PER ATC.

FLIGHT INSPECTED BY:

PROCESSED IAW AIRCRAFT OPS GRP (AJW-33) MEMO,
10/3/18, SUB: FLIGHT INSPECTION REVIEW NOT REQUIRED

OFFICE SYMBOL:

DATE:

Digitally signed by
ALLAN WILL
Dec 20, 2019

DEVELOPED BY:

PHILLIP BRANDENBURG

Digitally signed by
PHILLIP BRANDENBURG
Dec 19, 2019

OFFICE SYMBOL:

DATE:

AJV-A423 08/19/2019

APPROVED BY:

MARLON ROBINSON

OFFICE SYMBOL:

DATE:

AJV-A420

Digitally signed by
ALLAN WILL
Dec 20, 2019

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A	ALPA	AOPA	APA	HAI	NBAA
☒	☒	☒	☒	☐	☒

OTHER:

ZDV, BJC, ATCT, DEN APP CON, CO AERO MGR, AMGR'S

CHANGES - REASONS:

1. CHANGED ALL AIRPORT NAME REFERENCES FROM FRONT RANGE TO COLORADO AIR AND SPACE PORT, ID CHANGED FROM KFTG TO KCFO - PER FPT/APT REQUEST.

12/4/19: THIS IS A CORRECTED COPY OF THE FORM APPROVED ON 12/4/19.

1. 8260-15B, CORRECTED AIRPORT NAME IN AIRPORTS SERVED FROM COORADO AIR AND SPACE PORT TO COLORADO AIR AND SPACE PORT.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOKES		SEVEN		YOKES7.YOKES		SIX		07/11/2018	30 JAN 2020
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
DENVER INTL (KDEN)									
RW08 (AER)	395239.20N/1043944.03W	N	-	-	-	-			CG 400 FT PER NM TO 8000 THEN CG 285 FT PER NM TO 16000
	395237.10N/1043502.20W	-	-	VI	090.53	3.62			RECOMMENDED NAVAID: DENVER VOR/DME
LASSS	395439.55N/1042553.19W	Y	FB	CF	073.90	7.33	AT/BELOW 10000		
SPYCE	395816.57N/1042254.52W	Y	FB	TF	032.35	4.28			
TURBN	400321.45N/1042244.14W	Y	FB	TF	001.50	5.08			
CHICN	401131.87N/1043031.80W	Y	FB	TF	323.84	10.12	AT/ABOVE 14000		
KKIMM	401814.70N/1043000.94W	Y	FB	TF	003.36	6.72	AT/ABOVE 16000		
BTELN	402524.81N/1042304.66W	Y	FB	TF	036.48	8.91			
YOKES	403436.96N/1041414.14W	Y	FB	TF	036.21	11.40			
RW16L (AER)	395349.33N/1044112.50W	N	-	-	-	-			CG 400 FT PER NM TO 7000 THEN CG 260 FT PER NM TO 16000
5934 MSL	-	-	-	VA	180.51	-			
MUGBE	395437.37N/1045408.28W	Y	FB	DF	-	-	AT/BELOW 10000		
WAZEE	395810.17N/1045701.43W	Y	FB	TF	327.96	4.18			
LODOE	400459.71N/1045634.81W	Y	FB	TF	002.86	6.83			
RINKR	401157.47N/1044934.69W	Y	FB	TF	037.62	8.79	AT/ABOVE 14000		
ELCEE	401753.43N/1044037.56W	Y	FB	TF	049.10	9.06	AT/ABOVE 16000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	050.18	26.18			
RW16R (AER)	395344.87N/1044145.90W	N	-	-	-	-			CG 400 FT PER NM TO 7000 THEN CG 260 FT PER NM TO 16000
5934 MSL	-	-	-	VA	180.51				



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED	EFFECTIVE DATE
YOKES		SEVEN		YOKES7.YOKES		SIX		07/11/2018	30 JAN 2020
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
MUGBE	395437.37N/1045408.28W	Y	FB	DF	-	-	AT/BELOW 10000		
WAZEE	395810.17N/1045701.43W	Y	FB	TF	327.96	4.18			
LODOE	400459.71N/1045634.81W	Y	FB	TF	002.86	6.83			
RINKR	401157.47N/1044934.69W	Y	FB	TF	037.62	8.79	AT/ABOVE 14000		
ELCEE	401753.43N/1044037.56W	Y	FB	TF	049.10	9.06	AT/ABOVE 16000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	050.18	26.18			
RW17L (AER)	395153.83N/1043828.70W	N	-	-	-	-	CG 400 FT PER NM TO 7000 THEN CG 220 FT PER NM TO 15000		
	394830.14N/1043831.20W	-	-	VI	180.54	3.39	RECOMMENDED NAVAID: DENVER VOR/DME		
GISTT	394557.50N/1043501.10W	Y	FB	CF	133.30	3.71	AT/ABOVE 7000	AT/BELOW 250K	
KIDNG	394837.67N/1042339.58W	Y	FB	TF	073.00	9.15	AT/BELOW 1000		
GINTH	395616.09N/1042303.91W	Y	FB	TF	003.43	7.65	AT/BELOW 11000		
SPYCE	395816.57N/1042254.52W	Y	FB	TF	003.43	2.01			
TURBN	400321.45N/1042244.14W	Y	FB	TF	001.50	5.08			
CHICN	401131.87N/1043031.80W	Y	FB	TF	323.84	10.12	AT/ABOVE 14000		
KKIMM	401814.70N/1043000.94W	Y	FB	TF	003.36	6.72	AT/ABOVE 16000		
BTELN	402524.81N/1042304.66W	Y	FB	TF	036.48	8.91			
YOKES	403436.96N/1041414.14W	Y	FB	TF	036.21	11.40			
RW17R (AER)	395140.48N/1043936.56W	N	-	-	-	-	CG 455 FT PER NM TO 6500 THEN CG 220 FT PER NM TO 15000		
	394835.87N/1043938.78W	-	-	VI	180.53	3.07	RECOMMENDED NAVAID: DENVER VOR/DME		
GISTT	394557.50N/1043501.10W	Y	FB	CF	126.50	4.44	AT/ABOVE 7000	AT/BELOW 250K	

QUALITY
23
CHECKED

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED	EFFECTIVE DATE
YOKES		SEVEN		YOKES7.YOKES		SIX		07/11/2018	30 JAN 2020
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
KIDNG	394837.67N/1042339.58W	Y	FB	TF	073.00	9.15	AT/BELOW 10000		
GINTH	395616.09N/1042303.91W	Y	FB	TF	003.43	7.65	AT/BELOW 11000		
SPYCE	395816.57N/1042254.52W	Y	FB	TF	003.43	2.01			
TURBN	400321.45N/1042244.14W	Y	FB	TF	001.50	5.08			
CHICN	401131.87N/1043031.80W	Y	FB	TF	323.84	10.12	AT/ABOVE 14000		
KKIMM	401814.70N/1043000.94W	Y	FB	TF	003.36	6.72	AT/ABOVE 16000		
BTELN	402524.81N/1042304.66W	Y	FB	TF	036.48	8.91			
YOKES	403436.96N/1041414.14W	Y	FB	TF	036.21	11.40			
RW25 (AER)	395026.37N/1044102.17W	N	-	-	-	-			CG 425 FT PER NM TO 8000 THEN CG 270 FT PER NM TO 15000
	395028.13N/1044531.52W	-	-	VI	270.51	3.46			RECOMMENDED NAVAID: DENVER VOR/DME
MUGBE	395437.37N/1045408.28W	Y	FB	CF	302.01	7.82	AT/BELOW 10000		
WAZEE	395810.17N/1045701.43W	Y	FB	TF	327.96	4.18			
LODOE	400459.71N/1045634.81W	Y	FB	TF	002.86	6.83			
RINKR	401157.47N/1044934.69W	Y	FB	TF	037.62	8.79	AT/ABOVE 14000		
ELCEE	401753.43N/1044037.56W	Y	FB	TF	049.10	9.06	AT/ABOVE 16000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	050.18	26.18			
RW34L (AER)	395106.79N/1044147.72W	N	-	-	-	-			CG 465 FT PER NM TO 7000 THEN CG 240 FT PER NM TO 12000
	395502.75N/1044145.00W	-	-	VI	000.51	3.93			RECOMMENDED NAVAID: DENVER VOR/DME
IRIIS	400244.17N/1043517.48W	Y	FB	CF	032.83	9.15	AT/BELOW 10000		
VELAA	401642.41N/1042606.43W	Y	FB	TF	026.72	15.64	AT/ABOVE 12000		

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOKES		SEVEN		YOKES7.YOKES		SIX		07/11/2018	30 JAN 2020
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
RW34R (AER)	395150.77N/1044113.88W	N	-	-	-	-			CG 465 FT PER NM TO 7000 THEN CG 240 FT PER NM TO 12000
	395508.45N/1044111.59W	-	-	VI	000.51	3.29			RECOMMENDED NAVAID: DENVER VOR/DME
IRIIS	400244.17N/1043517.48W	Y	FB	CF	030.84	8.84	AT/BELOW 10000		
VELAA	401642.41N/1042606.43W	Y	FB	TF	026.72	15.64	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
RW35L (AER)	394941.93N/1043937.98W	N	-	-	-	-			CG 400 FT PER NM TO 7000 THEN CG 250 FT PER NM TO 12000
	395323.21N/1043935.32W	-	-	VI	000.53	3.69			RECOMMENDED NAVAID: DENVER VOR/DME
IRIIS	400244.17N/1043517.48W	Y	FB	CF	019.45	9.91	AT/BELOW 10000		
VELAA	401642.41N/1042606.43W	Y	FB	TF	026.72	15.64	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
RW35R (AER)	394955.27N/1043830.16W	N	-	-	-	-			CG 400 FT PER NM TO 7000 THEN CG 250 FT PER NM TO 12000
	395338.11N/1043827.42W	-	-	VI	000.54	3.71			RECOMMENDED NAVAID: DENVER VOR/DME
IRIIS	400244.17N/1043517.48W	Y	FB	CF	014.97	9.41	AT/BELOW 10000		
VELAA	401642.41N/1042606.43W	Y	FB	TF	026.72	15.64	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
CENTENNIAL	(KAPA)								
RW17L (AER)	393502.91N/1045105.31W	N	-	-	-	-			CG 255 FT PER NM TO 8000

QUALITY
23
CHECKED

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>		<u>NUMBER</u>		<u>DP COMPUTER CODE</u>		<u>SUPERSEDED NUMBER</u>		<u>DATED</u>	<u>EFFECTIVE DATE</u>
YOKES		SEVEN		YOKES7.YOKES		SIX		07/11/2018	30 JAN 2020
<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
6400 MSL	-	-	-	VA	177.95	-			
	-	-	-	VM	177.95	-			
VELAA	401642.41N/1042606.43W	Y	FB	DF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
RW17R (AER)	393444.35N/1045113.39W	N	-	-	-	-	CG 370 FT PER NM TO 8000		
6400 MSL	-	-	-	VA	177.95	-			
	-	-	-	VM	177.95	-			
VELAA	401642.41N/1042606.43W	Y	FB	DF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
RW35L (AER)	393335.23N/1045110.19W	N	-	-	-	-			
6400 MSL	-	-	-	VA	357.95	-			
	-	-	-	VM	357.95	-			
VELAA	401642.41N/1042606.43W	Y	FB	DF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
RW35R (AER)	393324.15N/1045100.76W	N	-	-	-	-			
6400 MSL	-	-	-	VA	357.95	-			
	-	-	-	VM	357.95	-			
VELAA	401642.41N/1042606.43W	Y	FB	DF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			

QUALITY
23
CHECKED

FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED	EFFECTIVE DATE
YOKES		SEVEN		YOKES7.YOKES		SIX		07/11/2018	30 JAN 2020
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
NORTHERN COLORADO RGNL (KFNL)									
VELAA	401642.41N/1042606.43W	Y	FB	IF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
COLORADO AIR AND SPACE PORT (KCFO)									
RW08 (AER)	394738.42N/1043354.88W	N	-	-	-	-			
6020 MSL	-	-	-	VA	091.15				
	-	-	-	VM	091.15				
VELAA	401642.41N/1042606.43W	Y	FB	DF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
RW17 (AER)									
RW17 (AER)	394708.14N/1043127.25W	N	-	-	-	-			
6020 MSL	-	-	-	VA	179.99	-			
	-	-	-	VM	179.99	-			
VELAA	401642.41N/1042606.43W	Y	FB	DF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.60			
RW26 (AER)									
RW26 (AER)	394736.82N/1043212.42W	N	-	-	-	-			
6020 MSL	-	-	-	VA	271.17	-			
	-	-	-	VM	271.17	-			
VELAA	401642.41N/1042606.43W	Y	FB	DF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			



FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)

DP NAME		NUMBER		DP COMPUTER CODE		SUPERSEDED NUMBER		DATED	EFFECTIVE DATE
YOKES		SEVEN		YOKES7.YOKES		SIX		07/11/2018	30 JAN 2020
FIX/NAVAID	LAT/LONG	C	FO/FB	LEG TYPE	TC	DIST (NM)	ALTITUDE	SPEED	REMARKS
RW35 (AER)	394549.10N/1043127.23W	N	-	-	-	-			
6020 MSL	-	-	-	VA	359.99	-			
	-	-	-	VM	359.99	-			
VELAA	401642.41N/1042606.43W	Y	FB	DF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
ROCKY MOUNTAIN METROPOLITAN		(KBJC)							
VELAA	401642.41N/1042606.43W	Y	-	IF	-	-	AT/ABOVE 12000		
YOKES	403436.96N/1041414.14W	Y	FB	TF	026.80	20.06			
YOKES	403436.96N/1041414.14W	Y	-	IF	-	-			YOKES7.BFF
COPLA	404940.37N/1040545.41W	Y	FB	TF	023.15	16.37			
BFF VORTAC	415338.99N/1032855.31W	Y	FB	TF	023.25	69.70			
YOKES	403436.96N/1041414.14W	Y	-	IF	-	-			YOKES7.CHICI
CHICI	412351.84N/1031022.28W	Y	FB	TF	044.15	69.00			

