

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH			
FROM	TO	COURSE AND DISTANCE	ALTITUDE				
FETIV (IAF)	HUKAM (NOPT) (FB)	090.83 / 5.00	3600	LPV: DA LNAV: RW18 CLIMB TO 3600 DIRECT JUNLI AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 000.82 INBOUND. CHART FAS OBST: 1560 TOWER 374514N/0971353W CHART A-683. CHART BEECH FACTORY AIRPORT. CHART CESSNA AIRCRAFT FIELD. CHART MCCONNELL AFB. DISTANCE TO THLD FROM 266 HAT: 0.73 NM. CHART VDP AT 1.17 MILES TO RW18* LNAV ONLY. WAAS CHANNEL # 81808 REFERENCE PATH ID: W18A DISTANCE TO THLD FROM 266 HAT: 0.73NM			
HENEV (IAF)	HUKAM (NOPT) (FB)	270.95 / 5.00	3600				
HUKAM (IF/IAF)	DEYEK (FB)	180.88 / 6.02	3000				

1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF)	
2. HOLD N HUKAM, RT, 180.88 INBOUND, 3600 FT. IN LIEU OF PT (IAF)	
3. FAC: <u>180.86</u> FAF: <u>DEYEK</u>	DIST FAF TO MAP: <u>4.81</u> THLD: <u>4.81</u>
4. MIN. ALT: <u>HUKAM 3600, DEYEK 3000</u>	
5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u>	
6. MIN GS INCPT: <u>3000</u> GS ALT AT: <u>DEYEK 3000</u> OM: <u> </u> MM: <u> </u> IM: <u> </u>	
7. GS ANGLE: <u>3.00</u> TCH: <u>45.2</u> 34:1 IS CLEAR	
8. MSA FROM: <u> </u>	

MINIMUMS															
TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	1680	1/2	266	1680	1/2	266	1680	1/2	266	1680	1/2	266			
NAV MDA	1820	1/2	406	1820	1/2	406	1820	3/4	406	1820	1	406			
CIRCLING	1880	1	459	1880	1	459	1880	1 1/2	459	2120	2 1/4	699			

NOTES: CHART NOTE: FOR INOPERATIVE MALS, INCREASE LPV ALL CATS VISIBILITY TO 1 MILE AND LNAV CAT D VISIBILITY TO 1 1/4. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE WICHITA MID-CONTINENT ALTIMETER SEE 8260-10		@ CAT D 800-2 1/4 @ NA WHEN LOCAL WEATHER NOT AVAILABLE.	QUALITY 1 CHECKED
CITY AND STATE	ELEVATION: 1421 TDZE: 1414	FACILITY IDENTIFIER: RNAV	
WICHITA, KS	AIRPORT NAME: COLONEL JAMES JABARA	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 18, ORIG-C 29 JUL 2010	
		SUP: AMDT: ORIG-B DATED 06/04/2009	

TL10-15 Pub 7/29/10