U.S. Department of Transportation
Federal Aviation Administration

RNAV STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

FROM	TO	COURSE AND DISTANCE	ALTITUDE
OBK VOR/DME	OMHUC WP (TF)(FB)	308.52 / 17.12	2500
WIPED INT	NOVCU WP (TF) (FB)	192.65 / 16.30	2500
NOVCU WP (IAF)	OMHUC WP (TF)(FB)(NoPT)	207.50 / 5.00	2500
SEJLE WP (IAF)	OMHUC WP (TF)(FB)(NoPT)	027.44 / 5.00	2500
OMHUC WP (IF/IAF)	IHOHY WP (TF)(FB)	117.47 / 5.54	2500

MISSED APPROACH

MAP: JEJTY WP

CLIMB TO 2000, THEN CLIMBING LEFT TURN TO 2500 DIRECT OMHUC WP AND HOLD.

ADDITIONAL FLIGHT DATA:
FAS OBST: 987 RIG 422122 / 880819

1. PT NA SIDE OF COURSE ____ OUTBOUND ____ FT WITHIN ____ MILES OF ____ (IAF)
2. **HOLD NW OMHUC WP, RT, 117.47 INBOUND, 2500 FT IN LIEU OF PT (IAF)**
3. FAC: 117.55 FAF: **IHOHY WP** DIST FAF TO MAP: - THLD: -
4. MIN. ALT: **OMHUC WP 2500, IHOHY WP 2500**
5. DIST TO THLD FROM OM: ____ MM: ____ IM: ____ 150 HAT: ____ 100 HAT: ____ GS ANT: ____
6. MIN GS INCPT: ____ GS ALT AT: ____ OM: ____ MM: ____ IM: ____
7. GS ANGLE: ____ TCH: ____
8. MSA FROM: **JEJTY WP 2600**

MAG VAR: **2W** EPOCH YEAR: **95**

MINIMUMS

TAKEOFF: [ ] STANDARD [X] SEE FAA FORM 8260-15 FOR THIS AIRPORT ALTERNATE: N A [X]

CATEGORY	A			B			C			D			E		
	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA	DH/ MDA	VIS	HAT/HAA
CIRCLING	1380	1	592	1380	1	592	1380	1 1/2	592		NA				

NOTES: **USE CHICAGO O'HARE ALTIMETER SETTING.**

CITY AND STATE	ELEVATION: 788 TDZE: AIRPORT NAME:	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
GRAYSLAKE, IL.	CAMPBELL	GPS	P: JUN 15 2000 RNAV - B, ORIG	AMDT: NONE
				DATED