

**Federal Aviation
Administration**

Transmittal Letter 20-19

July 24, 2020

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
9/10/2020	TX	Amarillo	Rick Husband Amarillo Intl	0/7239	7/8/2020	RNAV (GPS) Y RWY 13, Amdt 1

AIRAC Date: 10 SEPTEMBER 2020

FDC 0/7239 AMA IAP RICK HUSBAND AMARILLO INTL, AMARILLO, TX. RNAV (GPS) Y RWY 13, AMDT 1... CHART CIRCLING ICON. CIRCLING CAT C MDA 4240/HAA 633 VIS 1 3/4, CAT D MDA 4280/HAA 673 VIS 2 1/4. ALTERNATE MINIMUMS: STANDARD, EXCEPT CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE NOTE: DME/DME RNP-0.3 NA. ADD PBN REQUIREMENTS NOTE: RNP APCH. CHANGE BARO-VNAV NOTE TO READ: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -22C OR ABOVE 41C. DELETE ALTIMETER SETTING NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BORGER ALTIMETER SETTING AND INCREASE ALL DA 153 FEET AND ALL MDA 160 FEET, INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/2 MILE, LNAV CATS C AND D VISIBILITY 1/2 MILE, CIRCLING CAT C VISIBILITY 1/4 MILE. DELETE NOTE: BARO-VNAV AND VDP NA WITH BORGER ALTIMETER SETTING. THIS IS RNAV (GPS) Y RWY 13, AMDT 1A. 2007081808-PERM