

US DEPARTMENT OF TRANSPORTATION
FEDERAL AVIATION ADMINISTRATION

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE
FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
SIDER	JADKI (FB)	026.68 / 11.96	6100	LPV: DA LNAV/VNAV: DA LNAV: RW13
UKDEW	RAXIE (FB)	269.71 / 17.26	6100	
RAXIE (IAF)	WEGES (FB)	219.41 / 6.00	6100	CLIMB TO 5400 DIRECT PAMPE AND ON TRACK 104.55 TO CAUDE AND HOLD.
JADKI (IAF)	WEGES (FB)	039.31 / 6.00	6100	
WEGES (IF)	CEMTU (FB)	129.36 / 3.89	5600	
CEMTU	MOVEO (FB)	129.36 / 2.71	5400	

ADDITIONAL FLIGHT DATA:
HOLD SE, RT, 298.27 INBOUND.
CHART FAS OBST: 3724 ATCT 351354N/1014223W
CHART P-47.
DISTANCE TO THLD FROM 200 HAT: 0.46 NM.
CHART VDP AT 1.02 MILES TO RW13* *LNAV ONLY.
WAAS CHANNEL # 57919
REFERENCE PATH ID: W13A
CHART ASR.

- PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- PROFILE STARTS AT WEGES
- FAC: 129.42 FAF: MOVEO DIST FAF TO MAP: 5.40 THLD: 5.40
- MIN. ALT: WEGES 6100, CEMTU 5600, MOVEO 5400, ZOTEN/2.00 NM TO RW13 4280*
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: 5400 GS ALT AT: MOVEO 5400 OM: MM: IM:
- GS ANGLE: 3.00 TCH: 52.4 34:1 IS CLEAR
- MSA FROM: RW13 6100

MAG VAR: 8E EPOCH YEAR: 2000

MINIMUMS

TAKEOFF:	STANDARD	X	SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A	STANDARD @										
CATEGORY =====>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LPV DA	3803	3/4	200	3803	3/4	200	3803	3/4	200	3803	3/4	200			
LNAV/VNAV DA	3976	1 1/4	373	3976	1 1/4	373	3976	1 1/4	373	3976	1 1/4	373			
LNAV MDA	3980	1	377	3980	1	377	3980	1	377	3980	1 1/4	377			
CIRCLING	4080	1	473	4080	1	473	4080	1 1/2	473	4240	2	633			

NOTES:
CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -22C (-7F) OR ABOVE 41C @ NA WHEN LOCAL WEATHER NOT AVAILABLE.
(105F).
CHART NOTE: DME/DME RNP-0.3 NA.
*LNAV ONLY
SEE 8260-10

CITY AND STATE AMARILLO, TX	ELEVATION: 3607 TDZE: 3603 AIRPORT NAME: RICK HUSBAND AMARILLO INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 13, AMDT 1 13 JAN 2011	SUP: RNAV (GPS) RWY 13 AMDT: ORIG DATED 03/20/2003
---------------------------------------	--	-------------------------------------	--	---

**RNAV (GPS) - STANDARD
INSTRUMENT APPROACH PROCEDURE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES CONT.

CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE BORGER ALTIMETER SETTING AND INCREASE ALL DA 153 FEET AND ALL MDA 160 FEET, INCREASE LPV AND LNAV/VNAV ALL CATS VISIBILITY 1/2 MILE, LNAV CATS C AND D VISIBILITY 1/2 MILE, CIRCLING CAT C VISIBILITY 1/4 MILE.
CHART NOTE: BARO-VNAV AND VDP NA WITH BORGER ALTIMETER SETTING.
CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT SIDER ON V402 SOUTHWEST BOUND AND AT UKDEW ON V12-280 NORTHEAST BOUND.

CITY AND STATE AMARILLO, TX	ELEVATION: 3607 TDZE: 3603 AIRPORT NAME: RICK HUSBAND AMARILLO INTL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 13, AMDT 1 13 JAN 2011	SUP: RNAV (GPS) RWY 13
				AMDT: ORIG
				DATED: 03/20/2003

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KAMA
RUNWAY	RW13
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	Y
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W13A
LTP/FTP LATITUDE	351346.9015N
LTP/FTP LONGITUDE	1014148.8010W
LTP/FTP ELLIPSOIDAL HEIGHT	+10721
FPAP LATITUDE	351241.1400N
FPAP LONGITUDE	1014035.2800W
THRESHOLD CROSSING HEIGHT (TCH)	00052.4
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	0344
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	35.0

CRC REMAINDER

8FD3FE46

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K4
LTP ORTHOMETRIC HEIGHT	+10983
FPAP ORTHOMETRIC HEIGHT	+10983

CITY AND STATE AMARILLO, TX	ELEVATION: 3607 TDZE: 3603	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) Y RWY 13, AMDT 1 13 JAN 2011	SUP: RNAV (GPS) RWY 13
	AIRPORT NAME: RICK HUSBAND AMARILLO INTL			AMDT: ORIG
				DATED: 03/20/2003

