

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.													
TERMINAL ROUTES										MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LNAV: RW10							
MOLLY		SUSIQ (TF) (FO) (RNP 2.00)		243.27 / 16.05				9000		CLIMBING LEFT TURN TO 9000 DIRECT SUSIQ AND HOLD.							
CRATT (IAF)		SUSIQ (NOPT) (TF) (FB) (RNP 1.00)		166.20 / 8.92				9000									
SUSIQ (IF/IAF)		WAREG (TF) (FB) (RNP 1.00)		100.62 / 8.27				7000		ADDITIONAL FLIGHT DATA: HOLD W, RT, 100.62 INBOUND. CHART FAS OBST: 4329 200' PWR LINE 315341N/1064500W WAREG TO RW10: 3.07/43. CHART AIRPORT ELEV: 4113, TDZE 4112							
WAREG (FAF)		SAZAR/2.65 NM TO RW10 (TF) (FB) (RNP 0.30)		100.70 / 6.08													
SAZAR/2.65 NM TO RW10		RW10 (MAP) (TF) (FO) (RNP 0.30)		100.70 / 2.65													
(SEE FORM 8260-10)																	
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																	
2. HOLD W SUSIQ, RT, 100.62 INBOUND, 9000 FT. IN LIEU OF PT (IAF)																	
3. FAC: 100.70 FAF: WAREG DIST FAF TO MAP: 8.73 THLD: 8.73																	
4. MIN. ALT: SUSIQ 9000, WAREG 7000, SAZAR/2.65 NM TO RW10 5000																	
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																	
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																	
7. GS ANGLE: _____ TCH: 34:1 IS CLEAR																	
8. MSA FROM: RW10 10100																	
MAG VAR: 11E EPOCH YEAR: 1990																	
MINIMUMS																	
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A X							
CATEGORY ==>		A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA		
LNAV MDA	4700	1	588	4700	1	588	4700	1 3/4	588	4700	1 3/4	588					
CIRCLING	4760	1	647	4760	1	647	4760	1 3/4	647	4760	2	647					
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE EL PASO INTL ALTIMETER SETTING.																	
CITY AND STATE SANTA TERESA, NM		ELEVATION: 4113 TDZE: 4112 AIRPORT NAME: DONA ANA COUNTY INTL JETPORT				FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 10, ORIG-B 22 JUNE 2017				SUP: AMDT: ORIG-A DATED 04/13/2006					

QUALITY
31
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW10 (MAP)	4513 MSL (CA)		
4513 MSL	SUSIQ (DF) (FO) (RNP 1.00)		9000

CITY AND STATE

SANTA TERESA, NM

ELEVATION: 4113

TDZE: 4112

AIRPORT NAME:

DONA ANA COUNTY INTL JETPORT

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 10, ORIG-B

22 JUNE 2017

SUP:

AMDT:

DATED:

QUALITY
31
CHECKED

ORIG-A

04/13/2006