

**Federal Aviation
Administration**

Transmittal Letter 21-15

MAY 28, 2021

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7/15/2021	FL	Lake City	Lake City Gateway	1/4394	5/12/2021	RNAV (GPS) RWY 10, Orig-E

Airac Date: 15 JULY 2021

FDC 1/4394 LCQ IAP LAKE CITY GATEWAY, LAKE CITY, FL. RNAV (GPS) RWY 10, ORIG-E...
CIRCLING CAT C MDA 780/HAA 579, CAT D MDA 960/HAA 759, CAT D VIS 2 1/2. DELETE
NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. CHART NOTE: RWY 10
HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NA. DELETE NOTE: DME/DME RNP-0.3
NA. PBN REQUIREMENTS NOTE: RNP APCH-GPS. DELETE NOTE: WHEN LOCAL
ALTIMETER SETTING NOT RECEIVED, USE GAINESVILLE ALTIMETER SETTING AND
INCREASE ALL MDA 100 FEET; INCREASE LNAV CAT C/D AND CIR CAT C VISIBILITY 1/4
MILE. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE
GAINESVILLE ALTIMETER SETTING: INCREASE ALL MDAS 100 FEET; INCREASE LNAV
CAT C/D VISIBILITY 3/8 SM AND CIRCLING CAT C VISIBILITY 1/2 SM AND CAT D 1/4 SM.
ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/2, NA WHEN LOCAL
WEATHER NOT AVAILABLE. THIS IS RNAV (GPS) RWY 10, ORIG-F. 2105121236-PERM