

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.															
TERMINAL ROUTES												MISSED APPROACH							
FROM		TO		COURSE AND DISTANCE				ALTITUDE		LP: RW34 LNAV: RW34 CLIMBING LEFT TURN TO 3000 DIRECT ATVUW AND HOLD. ADDITIONAL FLIGHT DATA: FAS OBST: 631 AAO 445842N/0691245W 695 AAO 445645N/0691042W. WAAS CHANNEL # 65723 REFERENCE PATH ID: W34A IKMOW TO RW34: 3.00/40. LTP HAE: 134.6 M									
RAZZR		WUGES (FB)		053.68 / 37.75				3000											
WUGES (IAF)		ATVUW (NOPT) (FB)		018.00 / 8.24				3000											
BGR VORTAC (IAF)		ATVUW (NOPT) (FB)		298.84 / 8.60				3000											
ATVUW (IF/IAF)		IKMOW (FB)		337.37 / 6.04				2000											
IKMOW (FAF)		RW34 (MAP) (FO)		337.31 / 4.51															
RW34 (MAP)		933 MSL		337.31															
933 MSL		ATVUW (FO)						3000											
1. PT <u> </u> SIDE OF COURSE <u> </u> OUTBOUND <u> </u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. HOLD SE ATVUW, LT, 337.37 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: <u>337.31</u> FAF: <u>IKMOW</u> DIST FAF TO MAP: <u>4.51</u> THLD: <u>4.51</u> 4. MIN. ALT: <u>ATVUW 3000, IKMOW 2000</u> 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: <u>34:1 IS NOT CLEAR</u> 8. MSA FROM: <u>RW34 3900</u>																MAG VAR: 18W		EPOCH YEAR: 1995	
MINIMUMS																			
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT												ALTERNATE: N A ☐ X ☐							
CATEGORY =====>		A			B			C			D			E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA				
LP MDA	980	1	456	980	1	456		NA			NA								
LNAV MDA	1140	1	616	1140	1	616		NA			NA								
CIRCLING	1220	1	687	1320	1	787		NA			NA								
NOTES: CHART NOTE: PROCEDURE NA AT NIGHT. CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: USE BANGOR ALTIMETER SETTING, WHEN NOT RECEIVED USE AUGUSTA ALTIMETER SETTING AND (SEE FORM 8260-10)																			
CITY AND STATE		ELEVATION: 533 THRE: 524		AIRPORT NAME:		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE:				SUP:							
DEXTER, ME				DEXTER RGNL				RNAV (GPS) RWY 34, ORIG 28 JUL 2011				AMDT: NONE							
												DATED							

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):

INCREASE ALL MDA 40 FEET, INCREASE CIRCLING CAT B VISIBILITY 1/4 MILE.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT WUGES ON V-3 WESTBOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT RAZZR ON V-93 SOUTHWEST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS ON BGR VORTAC AIRWAY RADIALS 239 CW 038.

CITY AND STATE

DEXTER, ME

ELEVATION: 533

THRE: 524

AIRPORT NAME:

DEXTER RGNL

FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 34, ORIG

28 JUL 2011

SUP:

AMDT: NONE

DATED:

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

DATA FIELD

DATA

OPERATION TYPE 0
SBAS SERVICE PROVIDER IDENTIFIER 0
AIRPORT IDENTIFIER 1B0
RUNWAY RW34
APPROACH PERFORMANCE DESIGNATOR 0
ROUTE INDICATOR
REFERENCE PATH DATA SELECTOR 0
REFERENCE PATH IDENTIFIER (APPROACH ID) W34A
LTP/FTP LATITUDE 450006.8880N
LTP/FTP LONGITUDE 0691400.1175W
LTP/FTP ELLIPSOIDAL HEIGHT +01346
FPAP LATITUDE 450114.3800N
FPAP LONGITUDE 0691522.1000W
THRESHOLD CROSSING HEIGHT (TCH) 00040.0
TCH UNITS SELECTOR (METERS OR FEET USED) F
GLIDEPATH ANGLE (GPA) 03.00
COURSE WIDTH AT THRESHOLD 106.75
LENGTH OFFSET 1832
HORIZONTAL ALERT LIMIT (HAL) 40.0
VERTICAL ALERT LIMIT (VAL) 0.0

CRC REMAINDER

B94BAB34

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE K6
LTP ORTHOMETRIC HEIGHT +01597
FPAP ORTHOMETRIC HEIGHT +01597

CITY AND STATE
DEXTER, ME

ELEVATION: 533 THRE: 524
AIRPORT NAME:
DEXTER RGNL

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 34, ORIG
28 JUL 2011

SUP:
AMDT: NONE
DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible]

QUALITY
6
CHECKED

CITY AND STATE DEXTER, ME	ELEVATION: 533 THRE: 524 AIRPORT NAME: DEXTER RGNL	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./ AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 34, ORIG 28 JUL 2011	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

SUSAP 1B0 K6GRW34 0030083373 N45000689W069140012-0100 +0134600524000040075R

```
SUSAP 1B0 K6PR34 RW34 001 0000W34A0N4500068880W06914001175+013460300N4501143800W06915221000106751832000400F400000B94BAB34
SUSAP 1B0 K6PR34 RW34 002E +01597+01597LP 65723
```

SUSAP 1B0 K6SRW34 K6PG 0 18018003925 M

QUALITY
CHECKED

ELEVATION: 533 THRE: 524
AIRPORT NAME:

DEXTER RGNL

FACILITY IDENTIFIER:
RNAV

PROCEDURE NO./ AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 34, ORIG
28 JUL 2011

SUP:	
AMDT:	NONE
DATED:	