

**Federal Aviation
Administration**

Transmittal Letter 16-11

April 8, 2016

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DAT	SUBJECT
26-May-16	AK	Anvik	Anvik	5/9205	03/23/16	RNAV (GPS) RWY 35, Orig

AIRAC Date: 26 MAY 2016

FDC 5/9205 ANV IAP ANVIK, ANVIK, AK. RNAV (GPS) RWY 35, ORIG... LNAV MDA 780/HAT 490 ALL CATS, VISIBILITY CATS C/D 1 3/8. CIRCLING CATS A/B/C 840/HAA 543, CAT D MDA 860/HAA 563. DELETE NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HOLY CROSS ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET AND LNAV VISIBILITY CAT C 1/4 MILE AND CAT D 1/2 MILE. DELETE NOTE: WHEN VGSI INOPERATIVE, PROCEDURE NA AT NIGHT. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE HOLY CROSS ALTIMETER SETTING AND INCREASE ALL MDAS 120 FEET AND LNAV VISIBILITY CAT C/D 3/8 MILE, AND CIRCLING VISIBILITY CAT D 1/2 MILE. THIS IS RNAV (GPS) RWY 35, ORIG A. 1512172003-PERM