

**Federal Aviation
Administration**

Transmittal Letter 19-24

October 4, 2019

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows: EFFECTIVE UPON PUBLICATION						
AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
7-Nov-19	OR	McMinnville	Mc Minnville Muni	9/6038	9/27/19	RNAV (GPS) RWY 22, ORIG

AIRAC Date: 7 NOVEMBER 2019

FDC **9/6038** MMV IAP MC MINNVILLE MUNI, Mc Minnville, OR. RNAV (GPS) RWY 22, ORIG... DELETE CIRCLING MINIMUMS. CHART NOTE: FOR INOPERATIVE ALS, INCREASE LPV ALL CATS VISIBILITY TO 1 SM. DELETE NOTE: FOR INOPERATIVE MALSR, INCREASE LPV ALL CATS. VISIBILITY TO 1. CHART NOTE: FOR INOPERATIVE ALS WHEN USING AURORA STATE ALTIMETER SETTING, INCREASE LPV ALL CATS VISIBILITY TO 1 1/4 SM. DELETE NOTE: FOR INOPERATIVE MALSR WHEN USING AURORA STATE ALTIMETER SETTING INCREASE LPV VISIBILITY ALL CATS. TO 1 1/4. CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 48C. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 48C (118F). PBN REQUIREMENTS NOTE: RNP APCH. DELETE NOTE: DME/DME RNP-0.3 NA. CHART NOTE: PROCEDURE NA FOR ARRIVALS AT UBG VOR/DME ON V500 WESTBOUND AND ARRIVALS ON BTG VORTAC AIRWAY RADIALS 160 CW 194. DELETE NOTE: PROCEDURE NA FOR ARRIVALS AT UBG VOR/DME VIA V500 WESTBOUND AND ARRIVALS ON BTG VORTAC AIRWAY RADIALS 160 CW 194. MISSED APPROACH: CLIMB TO 4900 DIRECT OVUGE THEN ON 218 TRACK TO PUCIV AND HOLD, CONTINUE CLIMB-IN-HOLD TO 4900. THIS IS RNAV (GPS) RWY 22, ORIG-A. 1909261735-PERM