

**FEDERAL AVIATION ADMINISTRATION  
 FLIGHT STANDARDS SERVICE  
 RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE  
 TITLE 14 CFR PART 97.33**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated.  
 Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or feet RVR.

<u>AIRPORT ID</u> KRXE	<u>PROCEDURE NAME</u> RNAV (GPS) RWY 35	<u>ORIGINAL/AMENDMENT</u> 2	<u>CITY</u> REXBURG	<u>STATE</u> ID		
<u>AIRPORT ELEVATION</u> 4862	<u>TDZE</u> 4862	<u>SUPERSEDED</u> RNAV (GPS) RWY 35	<u>ORIGINAL/AMENDMENT</u> 1D	<u>DATED</u> 01/02/2020	<u>MAG VAR</u> 15E	<u>EPOCH YEAR</u> 1990
<u>FACILITY</u> RNAV	<u>COORDINATES OF FACILITIES</u>	<u>ACTUAL EFFECTIVE DATE</u> 20 APRIL 2023	<u>REQUIRED EFFECTIVE DATE</u> ROUTINE	<u>CANCEL/SUSPEND</u>		

**TERMINAL ROUTES**    [THIS IS A CORRECTED COPY OF A PROCEDURE ORIGINALLY PUBLISHED IN TL 23-09.](#)

FROM	FIX TYPE	TO	FIX TYPE	LEG TYPE	FO/FB	RNP	COURSE	DISTANCE	ALTITUDE
LUDIC	IAF	OKAVE	NOPT	TF	FB	1.00	265.85	12.00	8600
IDA VOR/DME	IAF	OKAVE	NOPT	TF	FB	1.00	049.68	10.84	8600
OKAVE	IF/IAF	JOGUN		TF	FB	1.00	350.54	8.34	6700
JOGUN	FAF	AVUBE/2.01 NM TO RW35		TF	FB	0.30	351.46	3.64	
AVUBE/2.01 NM TO RW35		RW35	MAP	TF	FO	0.30	351.46	2.01	
RW35	MAP	5900 MSL		CA			351.46		5900
5900 MSL		OKAVE		DF	FO	1.00			8600

**MISSED APPROACH**

**MAP:**

LNAV: RW35

**MISSED APPROACH INSTRUCTIONS:**

CLIMB TO 5900 THEN CLIMBING LEFT TURN TO 8600 DIRECT OKAVE AND HOLD.

**ALTERNATE MISSED APPROACH INSTRUCTIONS:**





