

US DEPARTMENT OF TRANSPORTATION  
FEDERAL AVIATION ADMINISTRATION

ILS - STANDARD  
INSTRUMENT APPROACH PROCEDURE  
TITLE 14 CFR PART 97.29

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES				MISSED APPROACH	
FROM	TO	COURSE AND DISTANCE	ALTITUDE		
ACO VOR/DME (IAF)	BUKIN INT/BSV 22.37 DME/RADAR	276.00 / 10.35 (BSV LR-009)	2800	ILS: DA LOC: 4.22 MILES AFTER DERBY OM/INT/BSV 15.36 DME OR AT BSV 11.14 DME FIX	
BUKIN INT/BSV 22.37 DME/RADAR (IF)	DERBY OM/INT/BSV 15.36 DME	189.47 / 7.02 (I-RGO)	2600	CLIMB TO 1700 THEN CLIMBING LEFT TURN TO 3000 DIRECT BSV VOR/DME AND HOLD, OR AS DIRECTED BY ATC.  ALTERNATE MA: CLIMB TO 2000 THEN CLIMBING LEFT TURN TO 3100 DIRECT ACO VOR/DME AND HOLD.	
				ADDITIONAL FLIGHT DATA: HOLD S, RT, 008.00 INBOUND. CHART ARRIVAL HOLDING AT ACO VOR/DME: HOLD E, RT, 272.00 INBOUND, 2800. CHART FAS OBST: 1303 TREE 405615N/0812633W 1399 AAO 410009N/0812610W CHART: ASR. CHART AKRON FULTON INTL LOM IN HALF-TONE.	

1. PT NA SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
2. PROFILE STARTS AT BUKIN
3. FAC: 189.47 FAF: DERBY OM/INT/BSV 15.36 DME DIST FAF TO MAP: 4.22 THLD: 4.22
4. MIN. ALT: BUKIN 2800, DERBY OM 2600\*, ZEVLO/BSV 12.26 DME 1620\*
5. DIST TO THLD FROM OM: 4.22 MM: - IM: - 150 HAT: - 100 HAT: - GS ANT: 971
6. MIN GS INCPT: 2700 GS ALT AT: GS INTCP 2700 OM: 2597 MM: - IM: -
7. GS ANGLE: 3.00 TCH: 52.8
8. MSA FROM: ACO VOR/DME 360-180 3600, 180-360 3100

MAG VAR: 7W EPOCH YEAR: 1985

MINIMUMS															
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT						ALTERNATE: N A			ILS: STANDARD			LOC: STANDARD		
CATEGORY ==>	A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
S-ILS 19	**1418	2400	200	**1418	2400	200	**1418	2400	200	**1418	2400	200			
S-LOC 19	1620	2400	402	1620	2400	402	1620	4000	402	1620	4000	402			
CIRCLING	1760	1	532	1760	1	532	1760	1 1/2	532	1780	2	552			
ZEVLO FIX MINIMUMS															
S-LOC 19	1560	2400	342	1560	2400	342	1560	2400	342	1560	4000	342			
CIRCLING	1760	1	532	1760	1	532	1760	1 1/2	532	1780	2	552			

NOTES:  
CHART NOTE: \*\*RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.  
\*LOC ONLY  
CHART PLANVIEW NOTE: HOLDING NOT REQUIRED FOR ARRIVALS ON ACO VOR/DME AIRWAY RADIALS 347 CW 185.  
CHART PLANVIEW NOTE: CAUTION: OM FOR AKRON INTL MAY BE RECEIVED APPROXIMATELY 5 MILES NORTH OF DERBY OM.



CITY AND STATE AKRON, OH	ELEVATION: 1228 TDZE: 1218 AIRPORT NAME: AKRON-CANTON RGNL	FACILITY IDENTIFIER: I-RGO	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 19, AMDT 8 13 JAN 2011	SUP: AMDT: 7B DATED 05/08/2008
-----------------------------	--	-------------------------------	--	--------------------------------------