

**Federal Aviation  
Administration**

**Transmittal Letter 21-07**

**February 5, 2021**

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53  
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure  
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA,  
LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME,  
MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:  
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
3/25/2021	TX	Longview	East Texas Rgnl	0/6937	12/16/2020	RNAV (GPS) RWY 18, Amdt 2A

**25 MARCH 2021**

FDC 0/6937 GGG IAP EAST TEXAS RGNL, LONGVIEW, TX. RNAV (GPS) RWY 18, AMDT 2A... CIRCLING CAT C MDA 980/HAA 614, CAT D MDA 1080/HAA 714, VISIBILITY CAT C 1 3/4 AND CAT D 2 1/4. DELETE NOTE: DME/DME RNP 0.3 NA. PBN REQUIREMENT NOTE: RNP APCH - GPS. DELETE NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C (5F) OR ABOVE 41C (105F). CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -15C OR ABOVE 41C. ALTERNATE MINIMUMS: STANDARD EXCEPT CAT D 800-2 1/4, NA WHEN LOCAL WEATHER NOT AVAILABLE. DELETE NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART NOTE: RWY 18 HELICOPTER VISIBILITY REDUCTION BELOW 3/4 SM NOT AUTHORIZED. CHANGE ALTIMETER NOTE TO READ: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE GILMER ALTIMETER SETTING AND INCREASE ALL DA 59 FEET AND ALL MDA 60 FEET; INCREASE LPV AND LNAV/ VNAV VISIBILITY ALL CATS 1/8 SM AND LNAV AND CIRCLING VISIBILITY CATS C/D 1/4 SM. THIS IS RNAV (GPS) RWY 18, AMDT 2B. 2011302236-PERM