

**Federal Aviation
Administration**

Transmittal Letter 22-25

October 14, 2022

**PREPARED BY THE AERONAUTICAL INFORMATION GROUP, AJV-53
(AVAILABLE ON THE WEB AT [HTTP://NFDC.FAA.GOV](http://NFDC.FAA.GOV))**

**The enclosed Standard Instrument Approach Procedures, Departure
Procedures/Takeoff Minimums and Fix Actions are effective as indicated.**

By amending: §97.23 VOR, VOR/DME, VOR or TACAN, and VOR/DME or TACAN; §97.25 LOC, LOC/DME, LDA, LDA/DME, SDF, SDF/DME; §97.27 NDB, NDB/DME; §97.29 ILS, ILS/DME, MLS, MLS/DME, MLS/RNAV; §97.31 RADAR SIAPs; §97.33 RNAV SIAPs; and §97.35 COPTER SIAPs, Identified as follows:
.....EFFECTIVE UPON PUBLICATION

AIRAC DATE	STATE	CITY	AIRPORT	FDC NUMBER	FDC DATE	SUBJECT
12/1/2022	VT	Burlington	Burlington Intl	2/2692	9/19/2022	ILS OR LOC/DME RWY 33, Amdt 1C

AIRAC Date: 1 DECEMBER 2022

FDC 2/2692 BTV IAP BURLINGTON INTL, BURLINGTON, VT. ILS OR LOC/DME RWY 33, AMDT 1C... CHANGE TDZE FROM 335 TO 334. S-ILS 33 DA 608/HAT 274, ALL CATS. S-LOC 33 MDA 1020/HAT 686 ALL CATS, S-LOC 33 VISIBILITY CATS A/B RVR 4000, CAT C/D/E 1 3/4. CIRCLING CATS A/B MDA 1020/HAA 685, CAT C MDA 1220/HAA 885, VISIBILITY CAT C 2 3/4. CHART NOTE: FOR INOPERATIVE ALS, INCREASE S-ILS 33 CAT A/B VISIBILITY TO RVR 4500 AND S-LOC 33 CAT E TO 2 SM. CHART DISTANCE VDP TO THRESHOLD 1.85 NM. CHART NOTE: RWY 33 HELICOPTER VISIBILITY REDUCTION BELOW RVR 4000 NOT AUTHORIZED. ALTERNATE MINIMUMS: ILS: STANDARD - NA WHEN CONTROL TOWER CLOSED, LOC: STANDARD - CAT C 900-2 3/4, CAT D, E 1100-3 - NA WHEN CONTROL TOWER CLOSED. DELETE NOTE: INOPERATIVE TABLE DOES NOT APPLY TO S-LOC 33 CATS C, D, AND E. DELETE NOTE: INOPERATIVE TABLE DOES NOT APPLY TO S-ILS ALL CATS. CHART VDP AT 1.68 DME. THIS IS ILS OR LOC/DME RWY 33, AMDT 1D. 2207141336-PERM