

RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33						Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.										
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO			COURSE AND DISTANCE			ALTITUDE		LPV: DA LNAV/VNAV: DA LNAV: RW11 CLIMB TO 600 THEN CLIMBING RIGHT TURN TO 3000 DIRECT OSUCA AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 020.93 INBOUND. CHART FAS OBST: 635 TERRAIN 563616N/1694343W. DISTANCE TO THLD FROM 300 HAT: 0.64 NM. WAAS CHANNEL # 42741 REFERENCE PATH ID: W11A CHART CIRCLING ICON. LTP HAE: 50.5 M						
JIRON (IAF)		EQQUP (NOPT) (TF) (FB) (RNP 1.00)			201.12 / 8.00			3000								
OSUCA (IAF)		EQQUP (NOPT) (TF) (FB) (RNP 1.00)			020.93 / 8.00			3000								
EQQUP (IF/IAF)		APOTE (TF) (FB) (RNP 1.00)			111.02 / 6.00			2100								
APOTE (FAF)		WIVOG/2.30 NM TO RW11 (TF) (FB) (RNP 0.30)			111.16 / 2.71											
WIVOG/2.30 NM TO RW11		RW11 (MAP) (TF) (FO) (RNP 0.30)			111.16 / 2.30											
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF) 2. HOLD W EQQUP, RT, 111.02 INBOUND, 3000 FT. IN LIEU OF PT (IAF) 3. FAC: 111.16 FAF: APOTE DIST FAF TO MAP: 5.01 THLD: 5.01 4. MIN. ALT: EQQUP 3000, APOTE 2100, WIVOG/2.30 NM TO RW11 1060* 5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____ 6. MIN GS INCPT: 2100 GS ALT AT: APOTE 2100 OM: _____ MM: _____ IM: _____ 7. GS ANGLE: 3.60 TCH: 55.5 34:1 IS CLEAR 8. MSA FROM: _____																
										MAG VAR: 7E			EPOCH YEAR: 2020			
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT								ALTERNATE: N A		STANDARD @						
CATEGORY =====>		A			B			C			D			E		
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LPV DA	428	1	300	428	1	300	428	1	300		NA					
LNAV/VNAV DA	957	2	829	957	2	829	957	2	829		NA					
LNAV MDA	900	1	772	900	1	772	900	2	772		NA					
CIRCLING	900	1	772	980	1 1/4	852	980	2 1/2	852		NA					
NOTES: CHART NOTE: FOR UNCOMPENSATED BARO-VNAV SYSTEMS, LNAV/VNAV NA BELOW -14C (7F) OR ABOVE 47C (117F). @ CAT B 900-2, CAT C 900-2 1/2 CHART NOTE: DME/DME RNP-0.3 NA. *LNAV ONLY CHART NOTE: CIRCLING NA N OF RWY 11-29. (CONTINUED ON PAGE 2)																
CITY AND STATE		ELEVATION: 128 TDZE: 128			FACILITY IDENTIFIER: RNAV			PROCEDURE NO./AMDT NO./EFFECTIVE DATE:			SUP:					
ST GEORGE, AK		AIRPORT NAME: ST GEORGE						RNAV (GPS) RWY 11, ORIG			AMDT: NONE					
								13 SEPTEMBER 2018			DATED					



**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

<u>FROM</u>	<u>TO</u>	<u>COURSE AND DISTANCE</u>	<u>ALTITUDE</u>
RW11 (MAP)	600 MSL (CA)	111.16	600
600 MSL	OSUCA (DF) (FO) (RNP 1.00)		3000

NOTES, (CONT.):

CHART NOTE: INOPERATIVE TABLE DOES NOT APPLY TO LPV ALL CATS AND LNAV CAT A.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV/VNAV ALL CATS VISIBILITY TO 2 1/2 SM.

CHART NOTE: FOR INOPERATIVE ALS, INCREASE LNAV CAT C VISIBILITY TO 2 1/2 SM.

TAA

	<u>FROM</u>	<u>TO</u>	<u>ALT</u>
1.	021/30 CW 201/30 (NOPT)	EQQUP (IF/IAF) (FB)	3000
2.	201/30 CW 291/30	JIRON (IAF) (FB)	3000
3.	291/30 CW 021/30	OSUCA (IAF) (FB)	3000

QUALITY
24
CHECKED

CITY AND STATE

ST GEORGE, AK

ELEVATION: 128

TDZE: 128

AIRPORT NAME:

ST GEORGE

 FACILITY
IDENTIFIER:

RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:

RNAV (GPS) RWY 11, ORIG

13 SEPTEMBER 2018

SUP:

AMDT: NONE

DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION**DATA FIELD****DATA**

OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	PAPB
RUNWAY	RW11
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W11A
LTP/FTP LATITUDE	563450.0925N
LTP/FTP LONGITUDE	1694028.6050W
LTP/FTP ELLIPSOIDAL HEIGHT	+00505
FPAP LATITUDE	563407.9600N
FPAP LONGITUDE	1693806.7555W
THRESHOLD CROSSING HEIGHT (TCH)	00055.5
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.60
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1232
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	50.0

CRC REMAINDER

AA68C78B

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	PA
LTP ORTHOMETRIC HEIGHT	+00390
FPAP ORTHOMETRIC HEIGHT	+00390

QUALITY
24
CHECKED

CITY AND STATE ST GEORGE, AK	ELEVATION: 128 TDZE: 128 AIRPORT NAME: ST GEORGE	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 11, ORIG 13 SEPTEMBER 2018	SUP:
				AMDT: NONE
				DATED: