

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.												
TERMINAL ROUTES										MISSED APPROACH						
FROM		TO		COURSE AND DISTANCE				ALTITUDE		JEJZO						
BILBE		HEKEL (TF) (FO) (RNP 2.00)		273.16 / 131.96				2000		CLIMBING RIGHT TURN TO 2100 DIRECT HEKEL AND HOLD.						
DIBWO		HEKEL (TF) (FO) (RNP 2.00)		287.81 / 29.43				2000								
SPY NDB/DME		HEKEL (TF) (FO) (RNP 2.00)		162.55 / 38.23				2100								
HEKEL (IF/IAF)		AJBOS (TF) (FB) (RNP 1.00)		068.85 / 6.00				1600								
AJBOS (FAF)		JEJZO (MAP) (TF) (FO) (RNP 0.30)		069.00 / 4.50						ADDITIONAL FLIGHT DATA: HOLD W, RT, 068.85 INBOUND. CHART FAS OBST: 396 TREE 563521N/1694106W. CHART CIRCLING ICON. FAC ALIGNED WITH RW11 THRESHOLD.						
(SEE FORM 8260-10)																
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)																
2. HOLD W HEKEL, RT, 068.85 INBOUND, 2000 FT. IN LIEU OF PT (IAF)																
3. FAC: 069.00 FAF: AJBOS DIST FAF TO MAP: 4.50 THLD: _____																
4. MIN. ALT: HEKEL 2000, AJBOS 1600																
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____																
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____																
7. GS ANGLE: _____ TCH: _____																
8. MSA FROM: JEJZO 2100																
MAG VAR: 7E EPOCH YEAR: 2020																
MINIMUMS																
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT										ALTERNATE: N A		STANDARD @				
CATEGORY ==>		A		B		C		D		E						
		DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING		760	1	632	980	1 1/4	852	980	2 1/2	852		NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: CIRCLING NA N OF RWY 11-29.																
@ CAT B 900-2, CAT C 900-2 1/2																
CITY AND STATE ST GEORGE, AK		ELEVATION: 128 AIRPORT NAME: ST GEORGE		TDZE:		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-D, AMDT 1 13 SEPTEMBER 2018				SUP: AMDT: ORIG-A DATED 09/25/2008				



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
JEJZO (MAP)	528 MSL (CA)	069.00	
528 MSL	HEKEL (DF) (FO) (RNP 1.00)		2100

QUALITY
24
CHECKED

CITY AND STATE
ST GEORGE, AK

ELEVATION: 128 TDZE:
AIRPORT NAME:
ST GEORGE

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS)-D, AMDT 1
13 SEPTEMBER 2018

SUP:
AMDT: ORIG-A
DATED: 09/25/2008