

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES										MISSED APPROACH					
FROM		TO		COURSE AND DISTANCE		ALTITUDE		LP: RW25 LNAV: RW25							
HAHNS		VAREQ (TF) (FB) (RNP 2.00)		221.12 / 9.03		11300		CLIMBING RIGHT TURN TO 10000 DIRECT STRIM AND HOLD, CONTINUE CLIMB-IN-HOLD TO 10000.							
VAREQ (IAF)		ALWEN (TF) (FB) (RNP 1.00)		221.01 / 3.42		10700									
ALWEN		CHEMO (TF) (FB) (RNP 1.00)		220.97 / 3.42		9300		ADDITIONAL FLIGHT DATA: HOLD W, RT, 071.88 INBOUND. CHART FAS OBST: 7020 TOWER 402917N/1072835W, 6464 TERRAIN 402939N/1072839W. 7133 AAO 403133N/1072209W. 6805 AAO 402948N/1072612W. WAAS CHANNEL # 93841 REFERENCE PATH ID: W25A CHART CIRCLING ICON. BUVHO TO RW25: 3.00/32. LTP HAE: 1874.4 M							
ECHOA (IAF)		LORIN (TF) (FB) (RNP 1.00)		260.81 / 8.53		10000									
LORIN (SEE FORM 8260-10)		WUXEK (TF) (FB) (RNP 1.00)		260.79 / 3.00		9700									
1. PT _____ SIDE OF COURSE _____ OUTBOUND _____ FT WITHIN _____ MILES OF _____ (IAF)										MAG VAR: 9E EPOCH YEAR: 2020					
2. PROFILE STARTS AT CHEMO															
3. FAC: 254.09 FAF: BUVHO DIST FAF TO MAP: 6.50 THLD: 6.50															
4. MIN. ALT: CHEMO 9300, ALZOY 8500, BUVHO 8300, ZEPAL/3.40 NM TO RW25 7300															
5. DIST TO THLD FROM OM: _____ MM: _____ IM: _____ 150 HAT: _____ 100 HAT: _____ GS ANT: _____															
6. MIN GS INCPT: _____ GS ALT AT: _____ OM: _____ MM: _____ IM: _____															
7. GS ANGLE: _____ TCH: 20:1 IS NOT CLEAR 34:1 IS NOT CLEAR															
8. MSA FROM: RW25 12900															
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A						@					
CATEGORY =====>		A		B		C		D		E					
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
LP MDA	6720	1	522	6720	1	522	6720	1 1/2	522	6720	1 1/2	522			
LNAV MDA	7280	1 1/4	1082	7280	1 1/2	1082	7280	3	1082	7280	3	1082			
CIRCLING	7280	1 1/4	1082	7320	1 1/2	1122	7720	3	1522	7720	3	1522			
NOTES: CHART NOTE: CIRCLING NA FOR CAT D S OF RWY 07-25. CHART NOTE: STRAIGHT-IN AND CIRCLING RWY 25 NA AT NIGHT. CHART NOTE: RWY 25 HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED. PBN REQUIREMENTS NOTE: RNP APCH. (CONTINUED ON PAGE 2)															
CITY AND STATE CRAIG, CO		ELEVATION: 6198 TDZE: 6198 AIRPORT NAME: CRAIG-MOFFAT		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 25, ORIG 24 MAY 2018						SUP: AMDT: NONE DATED			



US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
WUXEK	CHEMO (TF) (FB) (RNP 1.00)	260.75 / 4.36	9300
EGFAX (IAF)	ZADNA (TF) (FB) (RNP 1.00)	310.60 / 4.05	9600
ZADNA	CHEMO (TF) (FB) (RNP 1.00)	310.56 / 4.05	9300
CHEMO (IF)	ALZOY (TF) (FB) (RNP 1.00)	254.17 / 3.00	8500
ALZOY	BUVHO (TF) (FB) (RNP 1.00)	254.13 / 2.69	8300
BUVHO (FAF)	ZEPAL/3.40 NM TO RW25 (TF) (FB) (RNP 0.30)	254.09 / 3.10	
ZEPAL/3.40 NM TO RW25	RW25 (MAP) (TF) (FO) (RNP 0.30)	254.09 / 3.40	
RW25 (MAP)	6598 MSL (CA)	254.09	
6598 MSL	STRIM (DF) (FO) (RNP 1.00)		10000

NOTES, (CONT.):

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT HAHNS ON V524 NORTHEAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT ECHOA ON V101 EAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT EGFAX ON V220-328 SOUTHEAST BOUND.

QUALITY
24
CHECKED

CITY AND STATE CRAIG, CO	ELEVATION: 6198 AIRPORT NAME: CRAIG-MOFFAT	TDZE: 6198 RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 25, ORIG 24 MAY 2018	SUP:
				AMDT: NONE
				DATED:

**RNAV STANDARD INSTRUMENT APPROACH PROCEDURE
FLIGHT STANDARDS SERVICE - FAR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

FAS DATA BLOCK INFORMATION

<u>DATA FIELD</u>	<u>DATA</u>
OPERATION TYPE	0
SBAS SERVICE PROVIDER IDENTIFIER	0
AIRPORT IDENTIFIER	KCAG
RUNWAY	RW25
APPROACH PERFORMANCE DESIGNATOR	0
ROUTE INDICATOR	
REFERENCE PATH DATA SELECTOR	0
REFERENCE PATH IDENTIFIER (APPROACH ID)	W25A
LTP/FTP LATITUDE	402946.1375N
LTP/FTP LONGITUDE	1073041.9870W
LTP/FTP ELLIPSOIDAL HEIGHT	+18744
FPAP LATITUDE	402935.2555N
FPAP LONGITUDE	1073237.9035W
THRESHOLD CROSSING HEIGHT (TCH)	00032.0
TCH UNITS SELECTOR (METERS OR FEET USED)	F
GLIDEPATH ANGLE (GPA)	03.00
COURSE WIDTH AT THRESHOLD	106.75
LENGTH OFFSET	1048
HORIZONTAL ALERT LIMIT (HAL)	40.0
VERTICAL ALERT LIMIT (VAL)	0.0
 <u>CRC REMAINDER</u>	 9264E689

ADDITIONAL PATH POINT RECORD INFORMATION

ICAO CODE	K2
LTP ORTHOMETRIC HEIGHT	+18889
FPAP ORTHOMETRIC HEIGHT	+18889

QUALITY
24
CHECKED

CITY AND STATE CRAIG, CO	ELEVATION: 6198 AIRPORT NAME: CRAIG-MOFFAT	TDZE: 6198 CRAIG-MOFFAT	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 25, ORIG 24 MAY 2018	SUP:
					AMDT: NONE
					DATED: