

**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
DAVVY	TWO	DAVVY2.DAVVY	ONE	04/10/2008	28 FEBRUARY 2019

<u>TYPE:</u>	<u>OBSTACLE</u>	<u>COPTER</u>	<u>SID</u>	<u>SPECIAL</u>	<u>RNAV</u>
	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

DP ROUTE DESCRIPTION:

TAKEOFF RWY 34: CLIMB DIRECT OLOWI, THEN ON TRACK 345.54 TO DAVVY, THEN ON ASSIGNED ROUTE, MAINTAIN 16000.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

<u>TRANSITION NAME</u>	<u>TRANSITION COMPUTER CODE</u>	<u>FROM FIX/NAVAID</u>	<u>TO FIX/NAVAID</u>	<u>COURSE</u>	<u>DISTANCE</u>	<u>MEA</u>	<u>MOCA</u>	<u>CROSSING ALTITUDE/FIXES</u>
------------------------	-------------------------------------	----------------------------	--------------------------	---------------	-----------------	------------	-------------	------------------------------------

PROCEDURAL DATA NOTES:

NOTE: GPS REQUIRED.
NOTE: RNAV 1.
NOTE: RADAR REQUIRED.

TAKEOFF MINIMUMS:

RWY 16: NA, ATC.

RWY 34: STANDARD WITH MINIMUM CLIMB OF 337 FT PER NM TO 13200.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 34: POLE 10 FT FROM DER, 26 FT LEFT OF CENTERLINE, 2 FT AGL/9932 FT MSL. TREES BEGINNING 18 FT FROM DER, 462 FT RIGHT OF CENTERLINE, UP TO 9949 FT MSL.

CONTROLLING OBSTACLES:

RWY 34: 12475 FT MSL AAO 392245.00N/1062333.00W

LOST COMMUNICATIONS PROCEDURES:

ADDITIONAL FLIGHT DATA:

REFERENCE MAG VAR: KLXV 9E EPOCH YR: 2020
DME/DME ASSESSMENT NOT CONDUCTED

AIRPORTS SERVED:

<u>AIRPORT NAME</u>	<u>CITY</u>	<u>STATE</u>
LAKE COUNTY (KLXV)	LEADVILLE	CO

COMMUNICATIONS:

ASOS, UNICOM, CTAF, ATIS

FIXES AND/OR NAVAIDS:

REMARKS:



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
GRAPHIC DEPARTURE PROCEDURES (DP)**

Bearings, headings, courses, tracks and radials are magnetic. Elevations and altitudes are in feet, MSL. Altitudes are minimum altitudes unless otherwise indicated
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated.

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
DAVVY	TWO	DAVVY2.DAVVY	ONE	04/10/2008	28 FEBRUARY 2019

FLIGHT INSPECTED BY: *Digitally signed by*
THOMAS E MOLOKIE **DAVID DANNER**
Dec 21, 2018

OFFICE SYMBOL: FICO
DATE: 12/18/18

DEVELOPED BY: *Digitally signed by*
LONNIE EVERHART (RALPH MILLER) **DAVID DANNER**
Dec 21, 2018

OFFICE SYMBOL: AJV-5400
DATE: 07/30/2018

APPROVED BY: *Digitally signed by*
LONNIE EVERHART **DAVID DANNER**
Dec 21, 2018

OFFICE SYMBOL: AJV-5400
DATE:

REQUIRED EFFECTIVE DATE:

ROUTINE

COORDINATED WITH:

A4A	ALPA	AOPA	APA	HAI	NBAA
<input type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input checked="" type="checkbox"/>

OTHER:

ZDV, CO AERO, APT MGR

CHANGES - REASONS:

1. UPDATED MAGVAR FROM 11E TO 9 E - PER FPT REQUEST
2. MOVED OLOWI FROM POSITION 391539.63N/1061932.22W TO 391609.25N/1061938.27W - ALIGN WITH TRUE RWY BEARING/MEET CURRENT BUILD CRITERIA.
3. REWORDED DP ROUTE DESCRIPTION TO MEET CURRENT CRITERIA - 8260.46F.



**FEDERAL AVIATION ADMINISTRATION
FLIGHT STANDARDS SERVICE
DEPARTURE (DATA RECORD)**

<u>DP NAME</u>	<u>NUMBER</u>	<u>DP COMPUTER CODE</u>	<u>SUPERSEDED NUMBER</u>	<u>DATED</u>	<u>EFFECTIVE DATE</u>
DAVVY	TWO	DAVVY2.DAVVY	ONE	04/10/2008	28 FEBRUARY 2019

<u>FIX/NAVAID</u>	<u>LAT/LONG</u>	<u>C</u>	<u>FO/FB</u>	<u>LEG TYPE</u>	<u>TC</u>	<u>DIST (NM)</u>	<u>ALTITUDE</u>	<u>SPEED</u>	<u>REMARKS</u>
RW34 (AER)	391238.91N/1061852.32W	N	-	-	-				
LOWI	391609.25N/1061938.27W	Y	FB	DF	-	3.55			CG 337 FT/NM TO 13200
DAVVY	393220.97N/1062138.14W	Y	FB	TF	354.54	16.26			

