

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION	<b>ILS - STANDARD                  INSTRUMENT APPROACH PROCEDURE                  TITLE 14 CFR PART 97.29</b>	Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.
--	---	--

TERMINAL ROUTES				MISSED APPROACH
FROM	TO	COURSE AND DISTANCE	ALTITUDE	
ACO VOR/DME (IAF)	OCUGA INT/I-GGZ 13.02 DME	205.00 / 2.53	3000	ILS: DA LOC: 5.35 MILES AFTER EGGII INT/I-GGZ 5.20 DME OR AT I-GGZ 0.16 DME FIX  CLIMB TO 2500 THEN CLIMBING LEFT TURN TO 3000 DIRECT BSV VOR/DME AND HOLD, OR AS DIRECTED BY ATC.  ALTERNATE MA: CLIMB TO 2000 THEN CLIMBING LEFT TURN TO 3100 ON HEADING 101 AND ACO VOR/DME R-185 TO MINER/ACO 24.76 DME AND HOLD (DME REQUIRED).  ADDITIONAL FLIGHT DATA: HOLD S, RT, 008.00 INBOUND. CHART ARRIVAL HOLDING AT ACO VOR/DME: HOLD NE, RT, 205.00 INBOUND, 3000. CHART IN PLANVIEW: ALTERNATE MA HOLDING, HOLD S MINER/ACO 24.76 DME, RT, 004.86 INBOUND. CHART FAS OBST: 1321 TREE 405525N/0812531W FAS OBST: 1439 AAO 405901N/0812129W CHART: ASR. CHART I-GGZ DME ANTENNA IN PROFILE. CHART IN PLANVIEW: MINER/ACO 24.76 DME.
OCUGA INT/I-GGZ 13.02 DME (IF)	EGGII INT/I-GGZ 5.20 DME	234.48 / 7.82 (I-GGZ)	3000	

1. PT NA SIDE OF COURSE        OUTBOUND        FT WITHIN        MILES OF        (IAF)
2. PROFILE STARTS AT OCUGA
3. FAC: 234.48 FAF: EGGII INT/I-GGZ 5.20 DME DIST FAF TO MAP: 5.35 THLD: 5.35
4. MIN. ALT: OCUGA 3000, EGGII 3000, IZERU INT/I-GGZ 1.20 DME 1700\*
5. DIST TO THLD FROM OM:        MM:        IM:        150 HAT:        100 HAT:        GS ANT: 1030
6. MIN GS INCPT: 3000 GS ALT AT: EGGII 3000 OM:        MM:        IM:
7. GS ANGLE: 3.00 TCH: 45.4
8. MSA FROM: ACO VOR/DME 360-180 3600, 180-360 3100

MAG VAR: 7W                      EPOCH YEAR: 1985

MINIMUMS																
TAKEOFF:	SEE FAA FORM 8260-15A FOR THIS AIRPORT							ALTERNATE: N A	ILS: STANDARD			LOC: STANDARD				
CATEGORY =====>	A			B			C			D			E			
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
S-ILS 23	**1426	2400	200	**1426	2400	200	**1426	2400	200	**1426	2400	200				
S-LOC 23	1700	2400	474	1700	2400	474	1700	5000	474	1700	5000	474				
CIRCLING	1760	1	532	1760	1	532	1760	1 1/2	532	1780	2	552				
IZERU FIX MINIMUMS																
S-LOC 23	1580	2400	354	1580	2400	354	1580	2400	354	1580	4000	354				
CIRCLING	1760	1	532	1760	1	532	1760	1 1/2	532	1780	2	552				

NOTES:  
 \*LOC ONLY  
 CHART PLANVIEW NOTE: HOLDING NOT REQUIRED FOR ARRIVALS ON ACO VOR/DME AIRWAY RADIALS 065 CW 123.  
 CHART NOTE: \*\*RVR 1800 AUTHORIZED WITH USE OF FD OR AP OR HUD TO DA.

CITY AND STATE AKRON, OH	ELEVATION: 1228      THRE: 1226 AIRPORT NAME: AKRON-CANTON RGNL	FACILITY IDENTIFIER: I-GGZ	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: ILS OR LOC RWY 23, AMDT 11A 20 OCT 2011	SUP: AMDT: 11 DATED 01/13/2011
-----------------------------	---	-------------------------------	--	--------------------------------------



**U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION**  
**ILS STANDARD INSTRUMENT APPROACH PROCEDURE**  
**FLIGHT STANDARDS SERVICES - FAR PART 97.29**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 424-18 - ILS

ROUTES	TRANSITION	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
	ACO	ACO	010	IAF	FC		FB		205.0()	000.5	AA 03000	
	ACO	OCUGA	020		CF		FB		205.0()	002.0	AA 03000	
		OCUGA	010	FACF	IF		FB				AA 03000	GI 03000
		EGGII	020	FAF	CF		FB		234.0()	007.8	GI 03000	GS 03000
		RW23	030	MAP	CF		FO		234.0()	005.4	AT 01271	

MISSED APPROACH	FIX	SEQ	USE	PATH	TURN	FO/FB	RNP	MAG (TRUE)	DISTANCE	ALTITUDE	SPEED
		040		CA		FB		234.5()		AA 02500	
	BSV	050		DF		FO				AA 03000	
	BSV	060		HM	R	FO		008.0()	T01.0	AA 03000	

POINT DATA	WAYPOINT	LAT IN SECS	LONG IN SECS	LAT IN MINS	LONG IN MINS
	ACO	N410628.45	W0811205.44	N4106.474	W08112.091
	BSV	N404426.41	W0812555.72	N4044.440	W08125.929
	IGGZ (DME)	N405522.10	W0812602.04	N4055.368	W08126.034
	EGGII	N405850.06	W0812054.87	N4058.834	W08120.915
	OCUGA	N410406.62	W0811317.38	N4104.110	W08113.290
	RW23	N405513.09	W0812607.26	N4055.218	W08126.121
	IGGZ (LOC)	N405411.54	W0812735.69	N4054.192	W08127.595

RUNWAY DATA	RWY	THRESHOLD ELEVATION	TCH
	RW23	01226	45



CITY AND STATE <b>AKRON, OH</b>	ELEVATION: <b>1228</b> THRE: <b>1226</b>	FACILITY IDENTIFIER:	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE:	SUP:
	AIRPORT NAME: <b>AKRON-CANTON RGNL</b>	<b>I-GGZ</b>	<b>ILS OR LOC RWY 23, AMDT 11A</b>	AMDT: <b>11</b>
			<b>20 OCT 2011</b>	DATED: <b>01/13/2011</b>