

**U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)**

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BRYCE	TWO	BRYCE2.BRYCE	ONE	11/18/2010	10 MAR 2011

TYPE: OBSTACLE RNAV

DP ROUTE DESCRIPTION:

TAKEOFF RWY 3: CLIMB HEADING 032.73 TO 8100, THEN CLIMB TO 13300 DIRECT YAYDO AND LEFT TURN DIRECT BCE VORTAC...
TAKEOFF RWY 21: CLIMB HEADING 212.74 TO INTERCEPT COURSE 263.66 TO BCE VORTAC AND HOLD SW, RT, 045.36 INBOUND; CONTINUE CLIMB IN HOLD TO MEA FOR ROUTE OF FLIGHT...

... BEFORE PROCEEDING ON COURSE.

TRANSITION ROUTES (GRAPHIC DEPICTION ONLY):

Transition Name	Transition Computer Codes	From FIX/NAVAID	To FIX/NAVAID	Course	Distance	MEA	MOCA	Crossing Altitudes/Fixes

PROCEDURAL DATA NOTES/TAKEOFF MINIMUMS:

RWY 3, STANDARD WITH MINIMUM CLIMB OF 285 FEET PER NM TO 12100.
RWY 21, STANDARD WITH MINIMUM CLIMB OF 310 FEET PER NM TO 10500.

NOTE: GPS REQUIRED.
NOTE: RNAV1.

TAKEOFF OBSTACLES NOTES:

NOTE: RWY 3, VEHICLES ON ROAD BEGINNING 135 FT FROM DER, 374 FT LEFT OF CENTERLINE, 15 FT AGL/7588 FT MSL. FENCE 38 FT FROM DER, 377 FT RIGHT OF CENTERLINE, 8 FT AGL/7558 FT MSL. NOTE: RWY 21, FENCE 23 FT FROM DER, 375 FT LEFT OF CENTERLINE, 4 FT AGL/7593 FT MSL. FENCE 296 FT FROM DER, 530 FT RIGHT OF CENTERLINE, 4 FT AGL/7601 FT MSL. VEHICLES ON ROAD BEGINNING 49 FT FROM DER, 28 FT RIGHT OF CENTERLINE, 15 FT AGL/7623 FT MSL. MULTIPLE POLES BEGINNING 867 FT FROM DER, 706 FT RIGHT OF CENTERLINE, 39 FT AGL/7638 FT MSL.

CONTROLLING OBSTACLES:

RWY 3: 10799 FT MSL AAO 375138.35N/1115230.84W, 11000 FT MSL AAO 375440.90N/1115321.70W.
RWY 21: 9239 FT MSL AAO 374122.42N/1121810.01W, 9780 FT MSL AAO 373351.86N/1122042.01W, 10626 FT MSL AAO 375600.20N/1121203.64W.

OBSTACLES MANDATING ODP ROUTE DEVELOPMENT : RWY 3 – 11241 FT MSL AAO 380110.82N/1121247.15W, 10680 FT MSL TOWER 374547.00N/1115257.00W. RWY 21 – 11241 FT MSL AAO 380110.82N/1121247.15W, 10680 FT MSL TOWER 374547.00N/1115257.00W.

LOST COMMUNICATIONS PROCEDURES:



**U.S. DEPARTMENT of TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
GRAPHIC DEPARTURE PROCEDURE (DP)**

Bearings, headings, courses, tracks, and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation.
Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated. Graphic depictions attached.

DP Name	Number	DP Computer Code	Superseded Number	Dated	Effective Date
BRYCE	TWO	BRYCE2.BRYCE	ONE	11/18/2010	10 MAR 2011

ADDITIONAL FLIGHT DATA:

DME/DME ASSESSMENT NOT CONDUCTED.
REFERENCE MAG VAR: KBCE 14E EPOCH YR:1980.

AIRPORTS SERVED:

BRYCE CANYON

BRYCE CANYON, UT

COMMUNICATIONS:

ZLC ARTCC, CDC FSS

FIXES AND/OR NAVAIDS:

REMARKS:

RNAV ODP REQUESTED IN FLIGHT PROCEDURES OFFICE IFP CHECKLIST.

