

US DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION		RNAV - STANDARD INSTRUMENT APPROACH PROCEDURE TITLE 14 CFR PART 97.33		Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.											
TERMINAL ROUTES				MISSED APPROACH											
FROM	TO	COURSE AND DISTANCE	ALTITUDE	LNAV: RW13 CLIMB TO 3100 DIRECT RAKGU AND HOLD. ADDITIONAL FLIGHT DATA: HOLD SE, RT, 308.81 INBOUND. CHART FAS OBST: 1600 TREE 472701N/0980858W COLPU TO RW13: 3.04/40.											
UYTAG	CEVOX (FB)	044.38 / 18.92	4000												
UNIZY	OHDUP (FB)	278.36 / 17.66	4000												
CEVOX (IAF)	TOSLY (FB)	038.47 / 5.00	4000												
OHDUP (IAF)	TOSLY (FB)	218.59 / 5.00	4000												
TOSLY (IF)	MOCUX (FB)	128.53 / 6.03	3100												
MOCUX (FAF)	COLPU/2.00 NM TO RW13 (FB)	128.60 / 3.07													
COLPU/2.00 NM TO RW13 (SEE FORM 8260-10)	RW13 (FO) (MAP)	128.60 / 2.00													
1. PT <u>NA</u> SIDE OF COURSE <u>OUTBOUND</u> FT WITHIN <u> </u> MILES OF <u> </u> (IAF) 2. PROFILE STARTS AT TOSLY 3. FAC: <u>128.60</u> FAF: <u>MOCUX</u> DIST FAF TO MAP: <u>5.07</u> THLD: <u>5.07</u> 4. MIN. ALT: TOSLY 4000, MOCUX 3100, COLPU/2.00 NM TO RW13 2100 5. DIST TO THLD FROM OM: <u> </u> MM: <u> </u> IM: <u> </u> 150 HAT: <u> </u> 100 HAT: <u> </u> GS ANT: <u> </u> 6. MIN GS INCPT: <u> </u> GS ALT AT: <u> </u> OM: <u> </u> MM: <u> </u> IM: <u> </u> 7. GS ANGLE: <u> </u> TCH: 34:1 IS NOT CLEAR 8. MSA FROM: RW13 3500				MAG VAR: 6E EPOCH YEAR: 2000											
MINIMUMS															
TAKEOFF: SEE FAA FORM 8260-15A FOR THIS AIRPORT				ALTERNATE: N A X											
CATEGORY ==>	A			B			C			D			E		
DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	
LNAV MDA	1860	1	436	1860	1	436	1860	1 1/4	436		NA				
CIRCLING	1880	1	456	1880	1	456	1880	1 1/2	456		NA				
NOTES: CHART NOTE: DME/DME RNP-0.3 NA. CHART NOTE: VISIBILITY REDUCTION BY HELICOPTERS NA. CHART PROFILE NOTE: VGSI AND DESCENT ANGLES NOT COINCIDENT. CHART NOTE: WHEN LOCAL ALTIMETER SETTING NOT RECEIVED, USE JAMESTOWN ALTIMETER SETTING AND (SEE FORM 8260-10)															
CITY AND STATE COOPERSTOWN, ND		ELEVATION: 1424 TDZE: 1424 AIRPORT NAME: COOPERSTOWN MUNI		FACILITY IDENTIFIER: RNAV		PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG 18 NOV 2010				SUP: AMDT: NONE DATED					

QUALITY
5
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES, (CONT.):

FROM	TO	COURSE AND DISTANCE	ALTITUDE
RW13 (MAP)	1824 MSL	128.60	
1824 MSL	RAKGU (FO)		3100

NOTES, (CONT.):

INCREASE ALL MDA 100 FEET AND INCREASE LNAV CAT C VISIBILITY 1/4 MILE.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT UNIZY ON V561 NORTHEAST BOUND.

CHART PLANVIEW NOTE: PROCEDURE NA FOR ARRIVALS AT UYTAG ON V55 SOUTHWEST BOUND, AND V170 SOUTHBOUND.

CITY AND STATE
COOPERSTOWN, ND

ELEVATION: 1424 TDZE: 1424
AIRPORT NAME:
COOPERSTOWN MUNI

FACILITY
IDENTIFIER:
RNAV

PROCEDURE NO./AMDT NO./EFFECTIVE DATE:
RNAV (GPS) RWY 13, ORIG
18 NOV 2010

SUP:
AMDT: NONE
DATED:

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

[illegible][illegible]

SEGMENT	1	2	3	4	5	6	7	8	9	0	1	2	3
SUSAP S32 K3FR13	AUNIZY	010UNIZYK3EA0E	IF							18000		B JS	
SUSAP S32 K3FR13	AUNIZY	020OHDUPK3EA0E	A 020TF			27840177	+ 04000					B JS	
SUSAP S32 K3FR13	AUNIZY	030TOSLYK3EA0EE	B 010TF			21860050	+ 04000					B JS	
SUSAP S32 K3FR13	AUYTAG	010UYTAGK3EA0E	IF							18000		B JS	
SUSAP S32 K3FR13	AUYTAG	020CEVOXK3EA0E	A 020TF			04440189	+ 04000					B JS	
SUSAP S32 K3FR13	AUYTAG	030TOSLYK3EA0EE	B 010TF			03850050	+ 04000					B JS	
SUSAP S32 K3FR13	R	010TOSLYK3EA0E	I IF				+ 04000			18000		B JS	
SUSAP S32 K3FR13	R	020MOCUXK3EA1E	F 051TF			12850060	+ 03100				RW13 K3PGB	JS	
SUSAP S32 K3FR13	R	020MOCUXK3EA2WN		N		ALNAV						JS	
SUSAP S32 K3FR13	R	021COLPUK3EA0E	S 031TF			12860031	V 0210002111			-304		B JS	
SUSAP S32 K3FR13	R	030RW13 K3PGOGY	M 031TF			12860020	01462			-304		B JS	
SUSAP S32 K3FR13	R	040	0 M 010CA			1286	+ 01824					B JS	
SUSAP S32 K3FR13	R	050RAKGUK3EA0EY	010DF				+ 03100					B JS	
SUSAP S32 K3FR13	R	060RAKGUK3EA0EE	R020HM			30880040	+ 03100					B JS	

	1	2	3	4	5	6	7	8	9	0	1	2	3
RUNWAY	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890	1234567890

SUSAP S32 K3GRW13	0034991287 N47253413W098063923+0000					+0408901422000040060R							

QUALITY
4
CHECKED

SUP:	
AMDT:	NONE
DATED:	

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

CITY AND STATE COOPERSTOWN, ND	ELEVATION: 1424 TDZE: 1424 AIRPORT NAME: COOPERSTOWN MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS) RWY 13, ORIG 18 NOV 2010	SUP:
				AMDT: NONE
				DATED: