

U.S. DEPARTMENT OF TRANSPORTATION – FEDERAL AVIATION ADMINISTRATION
TAKEOFF MINIMUMS AND OBSTACLE DEPARTURE PROCEDURES (ODP)

Bearings, headings, courses, tracks and radials are magnetic. Elevation and altitudes are in feet MSL. Altitudes are minimum altitudes unless otherwise indicated.
Ceilings are in feet above airport elevation. Distances are in nautical miles. Visibilities are in statute miles or feet RVR unless otherwise indicated

City, State	Airport	Effective Date	Amdt. No.
SPARTA, WI	SPARTA/FORT MC COY	30 JUN 2011	2

TAKEOFF MINIMUMS:

RWY 11, 29: STANDARD

RWY 1: 400-1 ½

RWY 19: 500-2 ¾ WITH A MINIMUM CLIMB OF 217 FT PER NM TO 1800 OR STANDARD WITH MINIMUM CLIMB OF 425 FT PER NM TO 1500, OR 1100-2 ½ FOR CLIMB IN VISUAL CONDITIONS...

TEXTUAL DEPARTURE PROCEDURES:

RWY 1: CLIMB HEADING 030.34 TO 1600 BEFORE TURNING ON COURSE.

RWY 11: CLIMB HEADING 112.14 TO 1800 BEFORE TURNING ON COURSE.

RWY 19: CLIMB HEADING 195.42 TO 1500 BEFORE TURNING ON COURSE.

RWY 29: CLIMB HEADING 287.14 TO 1500 BEFORE TURNING ON COURSE.

FOR CLIMB IN VISUAL CONDITIONS, CROSS SPARTA/FORT MC COY AIRPORT AT OR ABOVE 1800 FT MSL BEFORE PROCEEDING ON COURSE.

TAKEOFF OBSTACLE NOTES:

NOTE: RWY 1: RISING TERRAIN BEGINNING 14 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 1019 FT MSL. TREES BEGINNING 73 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/1119 FT MSL. VEHICLES ON ROAD BEGINNING 1437 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 15 FT AGL/874 FT MSL.

NOTE: RWY 11: OL ON POLE 759 FT FROM DER, 232 FT LEFT OF CENTERLINE, 26 FT AGL/854 FT MSL. TREES BEGINNING 989 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/949 FT MSL.

NOTE: RWY 19: TREES BEGINNING 99 FT FROM DER, LEFT AND RIGHT OF CENTERLINE, UP TO 100 FT AGL/1239 FT MSL. RIDGE 8695 FT FROM DER, 2008 FT LEFT OF CENTERLINE, 0 FT AGL/1122 FT MSL.

NOTE: RWY 29: TREES BEGINNING 802 FT FROM DER, 31 FT LEFT OF CENTERLINE, UP TO 61 FT AGL/879 FT MSL. POLE 1447 FT FROM DER, 432 FT RIGHT OF CENTERLINE, 50 FT AGL/866 FT MSL.

CONTROLLING OBSTACLES:

RWY 1: 1119 FT MSL TREE, 435809.29N/0904342.21W, 1139 FT MSL 435815.70N/0904328.55W.

RWY 11: 1539 FT MSL AAO, 435421.64N/0903840.09W.

RWY 19: 1068 FT MSL TREE, 435620.25N/0904429.61W, 1299 FT MSL TREE, 425521.77N/0904405.27W, 1539 FT MSL AAO 435258.15N/0904607.01W.

RWY 29: 1559 FT MSL AAO, 440106.66N/0904718.56W.

VCOA: 1339 FT MSL TREE, 435435.37N/0904223.74W, 1579 FT AAO, 435416.65N/0904159.51W.

OBSTACLES MANDATING ROUTE DEVELOPMENT:

RWY 1: 1359 FT MSL AAO, 440112.75N/0904350.90W.

RWY 11, 19: 1579 FT MSL AAO, 435416.65N/0904159.51W.

RWY 29: 1259 FT MSL TREE, 435921.77N/0904735.93W.

