

**RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE
TITLE 14 CFR PART 97.33**

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

TERMINAL ROUTES

MISSED APPROACH

FROM	TO	COURSE AND DISTANCE	ALTITUDE	
HALEB (IF/IAF)	DISCI (FB)	280.12 / 6.43	2800	LNAV: RW27 CLIMBING LEFT TURN TO 3600 DIRECT WELKO AND HOLD. ADDITIONAL FLIGHT DATA: HOLD S, RT, 355.03 INBOUND. CHART FAS OBST: 929 TREE 435245N/0854543W DISCI TO RW27: 3.00/40. CHART CIRCLING ICON. CHART FREMONT MUNI AWOS.
DISCI (FAF)	FEXUP/2.70 NM TO RW27 (FB)	280.02 / 3.37		
FEXUP/2.70 NM TO RW27	RW27 (MAP) (FO)	280.02 / 2.70		
RW27 (MAP)	1228 MSL	280.02	3600	
1228 MSL	WELKO (FO)			

- PT SIDE OF COURSE OUTBOUND FT WITHIN MILES OF (IAF)
- HOLD E HALEB, RT, 280.12 INBOUND, 3000 FT. IN LIEU OF PT (IAF)
- FAC: 280.02 FAF: DISCI DIST FAF TO MAP: 6.07 THLD:
- MIN. ALT: **HALEB 3000, DISCI 2800, FEXUP/2.70 NM TO RW27 1720**
- DIST TO THLD FROM OM: MM: IM: 150 HAT: 100 HAT: GS ANT:
- MIN GS INCPT: GS ALT AT: OM: MM: IM:
- GS ANGLE: TCH: **34:1 IS NOT CLEAR**
- MSA FROM:

MAG VAR: **6W** EPOCH YEAR: **2020**

MINIMUMS

TAKEOFF: <u> </u> SEE FAA FORM 8260-15A FOR THIS AIRPORT	ALTERNATE: N A <input checked="" type="checkbox"/>														
CATEGORY =====>															
	A	B	C	D	E										
	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA	DH/MDA	VIS	HAT/HAA
CIRCLING	1400	1	572	1400	1	572	1400	1 1/2	572		NA				

NOTES:
 CHART NOTE: CIRCLING NA TO RWYS 5 AND 23.
 CHART NOTE: DME/DME RNP-0.3 NA.
 CHART NOTE: HELICOPTER VISIBILITY REDUCTION BELOW 1 SM NOT AUTHORIZED.
 CHART NOTE: USE FREMONT MUNI ALTIMETER SETTING.
 (CONTINUED ON PAGE 2)

CITY AND STATE BALDWIN, MI	ELEVATION: 828 TDZE: AIRPORT NAME: BALDWIN MUNI	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-A, ORIG 21 JULY 2016	SUP: 4 AMDT: C-NONE DATED:
--------------------------------------	---------------------------------------------------------------------	-------------------------------------	-------------------------------------------------------------------------------------	------------------------------------------------

QUALITY
4
CHECKED

US DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV - STANDARD
INSTRUMENT APPROACH PROCEDURE - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

NOTES, (CONT.):
 CHART NOTE: PROCEDURE NA AT NIGHT.

TAA	FROM	TO	ALT
1.	190/30 CW 010/30 (NOPT) 190/10 CW 010/10	190/10 CW 010/10 HALEB (IF/IAF) (FB)	4000 3000
2.	010/30 CW 190/30 010/10 CW 190/10	010/10 CW 190/10 HALEB (IF/IAF) (FO)	3600 3000

CITY AND STATE BALDWIN, MI	ELEVATION: 828 AIRPORT NAME: BALDWIN MUNI	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO./AMDT NO./EFFECTIVE DATE: RNAV (GPS)-A, ORIG 21 JULY 2016	SUP: 4
					AMDT: NONE
					DATED:

QUALITY
4
CHECKED

U.S. DEPARTMENT OF TRANSPORTATION - FEDERAL AVIATION ADMINISTRATION
RNAV (GPS) STANDARD INSTRUMENT APPROACH PROCEDURE
 FLIGHT STANDARDS SERVICES - TITLE 14 CFR PART 97.33

Bearings, headings, courses, and radials are magnetic. Elevations and altitudes are in feet, MSL, except HAT, HAA, TCH, and RA. Altitudes are minimum altitudes unless otherwise indicated. Ceilings are in feet above airport elevation. Distances are in nautical miles unless otherwise indicated, except visibilities which are in statute miles or in feet RVR.

ARINC SUMMARY - 7D3

ROUTES

TRANSITION	WPT SEQ	WPT NAME	LEG TYPE	FB/FO	RNP	MAG CRS	REC NAV	ANGLE	TURN DIR	CENTER FIX	TURN RADIUS	ALTITUDE DESCRIPTION & VALUE	SPEED LIMIT DESCRIPTION & VALUE	WPT DESCRIPTION CODE
HALEB	010	HALEB	HF	FO		280.1			R			AA 03000		EE A
	010	HALEB	IF	FB								AA 03000		E I
	020	DISCI	TF	FB	1.0	280.1						AA 02800		E F
	021	FEXUP	TF	FB	0.3	280.0		3.00				AA 01720 GS 01728		E S
	030	RW27	TF	FO	0.3	280.0		3.00				AT 00868		GY M
	040		CA	FB		280.0						AA 01228		M
	050	WELKO	DF	FO					L			AA 03600		EY
060	WELKO	HM	FO			355.0		R			AA 03000		EE	

POINTS

POINT NAME	LATITUDE	LONGITUDE
WELKO	N434623.60	W0860921.99
DISCI	N435203.74	W0854131.88
FEXUP	N435217.80	W0854610.45
HALEB	N435136.37	W0853239.95

RUNWAYS

RUNWAY	THRESHOLD LATITUDE	THRESHOLD LONGITUDE	THRESHOLD ELEVATION	PROCEDURE TCH
RW27	N435228.94	W0854953.88	00828	40

CITY AND STATE BALDWIN, MI	ELEVATION: 828	TDZE:	FACILITY IDENTIFIER: RNAV	PROCEDURE NO. / AMDT NO. / EFFECTIVE DATE: RNAV (GPS)-A, ORIG 21 JULY 2016	SUP: 4
	AIRPORT NAME: BALDWIN MUNI				AMDT: NONE
					DATED:

QUALITY
4
CHECKED